

### FEATURES

- 3U Bench Top or Rack mounted system
- Class AB linear GaN design
- Instantaneous ultra wide bandwidth
- Suitable for all single channel modulation standards
- Optional uP remote control & monitoring
- Built-in protection circuits
- High reliability and ruggedness



### ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	1.0 - 6.0 GHz	
Power Output Psat	150 Watt Min	
Power Output P1dB	100 Watt Min	CW
Power Gain	50 dB Min	
Power Gain Flatness	3 dB p-p Max	Constant input power
Gain Variation Over Temperature	±2.0 dB Max	
Input / Output Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	40dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Typ	At rated output
Spurious	-60 dBc Max	Non-harmonic
Operating Voltage	100 - 240 VAC	
Power Consumption	1500 Watt Max	At rated output
Input Power Protection	+8 dBm Max	<10 Sec without damage
Load VSWR Protection	∞ : 1	<1 minute at rated Pout

### ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensation

### MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 133.3 x 560 mm	3U
Weight	25 Kg. Max	
RF Connectors In/Out	Type-N Female	Front Panel Standard
AC Power	IEC 60320-C14 / 9-Pin D-Sub	Or equivalent
Cooling	Built in Fan Cooling	Variable speed
<b>OPTIONAL:</b> Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, Optional GPIB Interface	Remote Bluetooth application

### OUTLINE DRAWING

