

Megger.

L1070 and L1071
Portable Locator

L1070 and L1071 **Portable Locator**



- **Multiple frequencies**
- **Transmit/receive frequency (815 Hz, 8 kHz, 82 kHz)**
- **SONDE support**
- **Peak and null detection**
- **Passive 60 Hz**
- **Measures current flow in buried conductors**
- **Transmitter variable output power levels**
- **Push-button depth measurement**

DESCRIPTION

Unparalleled in capability, the L1070 and L1071 Portable Locators locate buried cable and pipe in various situations. Capable of locating long or short ranges, inductive or conductive, active or passive, the units deliver quick and accurate results with a user-friendly interface. Whereas the L1070 uses a disposable battery type, the L1071 requires a rechargeable one.

Operating the receiver at multiple frequencies optimizes performance for the specific needs of the user. Low frequency of 815 Hz provides longer range and reduced errors from adjacent cables, ideal for electric power services. High 82 kHz frequency will path locate past bad telephone bonds, locate underground stubs and permit inductive locating with either the optional flexible coupler or direct soil induction. A special design feature on both units allow the user to select and compare receiver information on two frequencies simultaneously, without having to return to the transmitter. Excellent passive 50/60 Hz locating will pinpoint active power lines and other utilities where AC is present without the use of the transmitter.

The portable locator also features SONDE detection and locating. By selecting this feature, the user is able to choose a SONDE that will match the same frequency and the receiver.

APPLICATIONS

Flexibility remains the key strength of reaching difficult, multi-point, grounded utility locating applications. Combining high power at low frequency virtually eliminates the false coupling into adjacent objects and allows the high transmitter power to burn a signal past

several grounds and into multiple distributed grounds. Multi-grounded electrical distribution service, continuously grounded water pipes, multi-grounded telephone shield wiring, highly capacitive, cathodically protected coated gas pipes and CATV systems all benefit from the flexibility of the L1070 and L1071.

Conductor current readout on the units give the user information on the amount of current flowing on the target conductor with correction for changes in depth. To trace the direction where the transmitter signal is divided or where it goes into the soil at an insulation ground fault, press the CURRENT button. This feature is useful in cathodically protected systems with ground faults.

An optional ground return probe allows ground fault detection on unshielded electric services or sheath faults on telephone services through the technique of voltage gradient.

FEATURES AND BENEFITS

- Multiple transmit/receive frequencies provide accurate long or short range locates.
- Push-button depth measurements up to 15 ft (4.6 m) quickly identify service depths prior to digging.
- Passive 60 Hz detection serves as an excellent safety feature for identifying live underground primary and secondary utility cables.
- AC circuits in common trench situations. Passive detection also allows convenient locating of energized electric services.
- High power at low frequency solves the difficult multi-point grounded utility locating problem.

SPECIFICATIONS

Transmitter

Operating Frequency: 82 kHz, 8 kHz, 815 Hz, and BOTH (815 Hz/82 kHz) simultaneously

Indicators

AC Load Resistance Measurement, Low Bat Indicator, Low Bat warning modulated on output signal every 20 seconds

Load Matching: Automatic from 5Ω to 2000Ω

Output Power

815 Hz and 8 kHz

Normal 0.6 W

High 2.0 W

82 kHz

Normal 0.2 W

High 1.0 W

BOTH (815 Hz/82 kHz)

Normal 0.12 W + .06 W

HIGH 1.33 W + 0.67 W

Battery Type

Disposable (Used in L1070)

Eight 1.5 V D size alkaline

Rechargeable (Used in L1071)

12 V, 7 Amp-Hour maintenance free, sealed lead-acid includes 120 V ac wall-mount charger for overnight charging. Optional 12 V automotive power pack for fast charging, or powering unit from a vehicle cigarette lighter jack.

Battery Life

Disposable

Continuous: 8 to 15 hours depending on load, frequency and power setting

Intermittent: 40 to 60 hours depending on load, frequency and power setting. 25% duty cycle average.

Rechargeable

Continuous: 10 to 20 hours depending on load, frequency and power setting

Intermittent: 50 to 70 hours depending on load, frequency and power setting. 25% duty cycle average.

Operating Temperature Range

-4° to +133° F (-20° to +55° C)

Dimensions

6.5 H x 6.32 W x 16 L in.

(15.2 H x 12.7 W x 40.6 L cm)

Weight

8 lb (3.6 kg) with alkaline D cells

11.5 lb (5.2 kg) with rechargeable batteries

Receiver

Operating Frequency: 815 Hz, 8 kHz, 82 kHz, 50/60~(PASSIVE)

Antenna Mode

Null-responding vertical coil

Peak-responding horizontal coil

Audio Indication: Variable pitch response on all frequencies

Current Measurement

Display indicated relative current simultaneously between any two selected cables for target cable verification in a multi-conductor environment

Operating and Storage Temperature Range

-4° to +133° F (-20° to +55° C)

Battery Type: Six 1.5 V C size alkaline

Battery Life

Continuous: 40 hours

Intermittent: 82 hours

Auto power shutoff after 10 minutes of nonuse

Signal Strength

Analog LCD Bargraph. Absolute Digital Signal Strength readout from 0 to 999

Gain Control: Up/Down button for automatic centering and manual control

Manual

Bubble-level triangulation for verification of automatic readout in congested environments. **Note:** Accuracy is dependent on site conditions, nonconcentric conductor shape, number of nearby conductors, and soil return currents.

Dynamic Range: 126 dB

Depth Measurement

Automatic: Push-button 3 digit readout to 15 ft in feet/inches, (optional meter/centimeters to 4.6 m)

Dimensions

9.4 H x 3.75 W x 30.3 L in.

(23.8 W x 9.3 W x 76.9 L cm)

Weight: 3 lb (1.36 kg)

ORDERING INFORMATION

Item (Qty)	Cat. No.
L1070 Portable Locator	651070
L1071 Portable Locator	651071
Included Accessories	
L1070: Receiver, transmitter, red/black cord, batteries, ground rod, instruction manual and soft carrying case	
L1071: Receiver, rechargeable transmitter, red/black cord, batteries, ground rod, AC charger, instruction manual and soft carrying case	
Optional Accessories	
Folding ground return probe (grounded fault locator)	651075
Flexible coupler (Inductive Coupler)	651076
DC charger (automotive) used with 651071	651078

UK
Archcliffe Road, Dover
CT17 9EN England
T (0) 1 304 502101
F (0) 1 304 207342

UNITED STATES
4271 Bronze Way
Dallas, TX 75237-1019 USA
T 1 800 723 2861
T 1 214 333 3201
F 1 214 331 7399

OTHER TECHNICAL SALES OFFICES
Norristown USA, Toronto CANADA,
Mumbai INDIA, Trappes FRANCE,
Sydney AUSTRALIA, Madrid SPAIN
and The Kingdom of BAHRAIN.

ISO STATEMENT
Registered to ISO 9001:2000 Reg no. Q 09250
Registered to ISO 14001 Reg no. EMS 61597
L1070_1071_DS_en_V13
www.megger.com
Megger is a registered trademark