# MICRO-OHMMETERS 200A Digital



## **Model 6292**



# Programmable test currents and test duration with data storage and report generation using included application software



### **► SPECIFICATIONS**

MODEL	6292	
ELECTRICAL		
Test Current Range	Adjustable from 20 to 200A (True DC)	
Resistance Range	0.1 $\mu\Omega$ to 2 $m\Omega$ 2 to 200 $m\Omega$ 200 $m\Omega$ to 1 $\Omega$	
Accuracy	cy $\pm 1\%$ of reading from $50\mu\Omega$ to $19$	
$\begin{array}{c} \text{Resolution} & 0.1 \mu\Omega \text{ to } 2 m\Omega \\ & 2 \text{ to } 200 m\Omega \\ & 200 m\Omega \text{ to } 1\Omega \end{array}$	0.1 $\mu\Omega$ (20 to 200A) 10 $\mu\Omega$ (25A @ 200 $m\Omega$ ) 1 $m\Omega$ (5A @ 1 $\Omega$ )	
Output Voltage 100Vac: 4.2V @ 200A   220Vac: 8.6V @ 200A		
Max. Load Resistance	100Vac: $20m\Omega$ @ 200A 220Vac: $42m\Omega$ @ 200A	
Measurement Method Four-terminal, Kelvin-type		
Adjustable Test Time	5 to 120 seconds or unlimited	
Memory	Stores up to 8000 measurements	
Power Supply 100 to 240Vac, 50/60Hz		





### **▶ FEATURES**

- Adjustable test currents from 5 to 200A
- Programmable test duration from 5 to 120 sec
- BSG Ground Test with optional current probe
- Accurately measures low contact resistance with test currents up to 200A
- Measures resistances from  $0.1\mu\Omega$  to  $1\Omega$
- Low resolution of  $0.1\mu\Omega$
- Cooling system to improve the number of sequential tests that can be performed
- Backlit display
- Measures objects with both sides grounded
- Stores up to 8000 test results
- Direct printout of measurement results using DataView® software and a PC
- Rugged and water-resistant case

#### ► PRODUCT INCLUDES

Set of 25 ft Kelvin clips (200A hippo), ground lead (green) with clamp, 5ft USB cable, 110V US power cord and 15A fuse (5 x 20mm) and quick start user guide.

#### **USB Drive**

USB drive supplied with DataView® software and user manual.



#### **►ACCESSORIES**

Catalog #2129.86 (optional)



CATALOG NO.	DESCRIPTION	
2129.83	Micro-Ohmmeter Model 6292 (200A, 120/230V, DataView® software)	
Accessories (Optional)		
2129.86	Current Probe Model MR6292	
2129.87	Lead – Set of 2, 50ft Color-coded Kelvin Leads with 3" C-Clamp (special order)	
2129.72	Lead – Replacement, Set of 2, 25ft Color-coded Kelvin Leads with Alligator Clamp	AEMC®