

Advanced Test Equipment Rentals www.atecorp.com 800-404-ATEC (2832)



Tel: (818) 998-0223 Fax: (818) 998-6892 sales@AHSystems.com www.AHSystems.com

SAS-573

High Gain Horn Antenna 26.5 GHz – 40 GHz

High gain and low VSWR horn antenna excellent for both immunity and emissions compliance testing.

Frequency Range:26.5 GHz - 40 GHz Antenna Factor (1 Meter)39.8 to 40.5 Gain (dBi)18.9 to 21.8 Maximum Continuous Power:10 Watts Max Radiated Field:150 V/m Beamwidth17° Impedance:50 W Connector:WR-28 to 2.9mm female Mounting Base:1⁄4 - 20 Thread, female

> Physical Dimensions: Length: 4.1 in. (10.4 cm) Width: 1.1 in. (2.8 cm) Height: 1.4 in. (3.6 cm) Weight: 0.1 lb.'s (0.05 kg)

Features

- Broad Frequency Range of 18 GHz to 26.5 GHz
- Linearly Polarized High Gain, Low VSWR
- Individually Calibrated
- Three year Warranty

The A.H. Systems' SAS-573 Horn Antenna is a broadband antenna that offers excellent performance over the frequency range of 26.5 GHz to 40 GHz. High gain, low VSWR, and input handling capability up to 50 watts make this horn antenna excellent for both radiated emissions and immunity testing.

Recommended Accessories

- PAM-2640 (Preamplifier)
- SAC-40G-1.5 (3 Meter Low Loss Cable)

