

Advanced Test Equipment Rentals www.atecorp.com 800-404-ATEC (2832)



Tel: (818) 998-0223 Fax: (818) 998-6892 sales@AHSystems.com www.AHSystems.com

AK-521F-7

Bilogical Antenna Kit 25 MHz - 7 GHz

For rapid deployment along with the mobility of small package, this Bilogical Antenna Kit provides an inexpensive solution to broadband applications.

Frequency Range: 25 MHz - 7000 MHz

Gain: 6 dBi

Maximum Continuous Power: 400 Watts

Impedance: 50Ω

Max Radiated Field: 100 V/m
Connector: N-Type, fem

Connector: N-Type, female
Mounting Base: 1/4 - 20 Thread, female

Physical Dimensions

Height: 22.2 in. (56.4 cm)
Width: 38.5 in. (97.8 cm)
Length: 39.0 in. (99.1 cm)
Weight: 4.5 lb.'s (2.04 kg)



Features

- Hybrid Log Periodic Biconical Antenna
- Wide Frequency Range of 25 MHz 7000 MHz
- Receive and Transmit
- Individually Calibrated (1, 3 and 10 Meter calibration included, horizontal polarization)
- FCC, MIL-STD, VDE and TEMPEST Testing
- Rugged Construction

The A.H. Systems' SAS-521F-7 Bilogical Antenna is one of our latest antennas, providing an inexpensive solution to wide band applications. Whether testing inside a shielded enclosure or outdoors, this antenna will display efficient performance characteristics through the frequency range of 25 MHz to 7000 MHz.

Included equipment

Model Number Frequency Range Description

SAS-521F-7 20 MHz - 7000 MHz Folding Bilogical Antenna SAC-211 up to 10 GHz 3 Meter N-N cable

BTE-510 -- Bilogical Tripod Extension
TSC-521 -- Antenna Transit Storage Case

Case size:28" x 23" x 10" (71cm x 58cm x 25cm)

Kit weight:26 lbs. (11.8kg)

Recommended Accessories

- PAM-0207 (Preamplifier)
- SAC-211 (3 meter N/N Cable, RG-214U)
- ATU-510 (Antenna Tripod Unit, wooden)
- AEH-510 (Azimuth and Elevation Head, Plastic)





Tel: (818) 998-0223 Fax: (818) 998-6892 sales@AHSystems.com www.AHSystems.com



