



AMP4066-LC SOLID STATE HIGH POWER AMPLIFIER



FEATURES

- Designed for EMI/RFI, lab, CW/Pulse and all communication applications
- Small form factor, rack mounted system
- Class A/AB Linear design
- High Power Advanced technology devices
- Instantaneous ultra-wide bandwidth
- Built-in protection circuits, with extensive monitoring
- Local LCD & remote flexible interfaces
- High efficiency, with unprecedented reliability and ruggedness

ELECTRICAL SPECIFICATIONS: 25°C, 50Ω

Parameter	Specification	Notes
Operating Frequency Range	26.5 - 40.0 GHz	
Power Output @ Psat	40 Watt Typ	CW or Pulse
Power Output @ P1dB	20 Watt Min	35 Watt Typ
Power Gain	46 dB Min	0dBm or less for rated Pout
Power Gain Flatness	4.0 dB p-p Max	Constant input power
Gain Adjustment Range	20 dB Min	Local or Remote capable
Input Return Loss	-10 dB Max	
2-Tone Intermodulation (IMD)	-30 dBc Typ	36dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Max	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	100 - 240 VAC	47-63 Hz
Power Consumption	1500 Watt Typ	At rated output
Input Power Protection	+3 dBm Max ¹	
Load VSWR Protection	4 : 1: Max ²	Foldback @ preset limit
Sample Port (optional)	-40 dB	2.9mm K-Female

1 Units with optional digital monitor and control, for basic units <10 Sec without damage

2 Units with optional digital monitor and control, for basic units <1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non-condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport ³	

3 MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 266 x 600 mm	6U, excluding handles
Weight	33 Kg. Nom	
RF Connectors In/ Out / Sample (optional)	2.9 mm-F / WR28 / 2.9mm-F	Front or rear panel
Interface Connector	9-Pin D-Sub	Rear panel
AC Power	IEC 60320-C14	Or equivalent
Cooling: Built in Quiet-Cool	Close circuit Air-liquid cooling	
OPTIONAL: Digital Monitor & Control (DMC) FWD, REV, VSWR, GAIN, ALC, V & I, TEMP, Optional Safety Interlock (INT)	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface Open=STBY/Short=RFON	IEEE rear panel BNC-F rear panel

e

AMP4066-LC SOLID STATE HIGH POWER AMPLIFIER

AVAILABLE SPECIAL OPTIONS

Parameter	Specification	Notes
Option FRS: Forward RF Sample	-50dB, Type K-Female	Front or rear panel
Option RRS: Reflected RF Sample	-40dB, Type K-Female	Front or rear panel
Option GPIB: GPIB remote control	GPIB IEEE-488 Remote capability	
Included CPM: Calibrated Power Monitoring (With purchase of Option DMC)	Offset correction entry for +/- 0.2dB accuracy	7-points standard ⁴

⁴ Consult with factory if additional points would be required.

OUTLINE DRAWING SHOWN WITH LCD DIGITAL CONTROLLER

