

## Advanced Test Equipment Corp. www.atecorp.com 800-404-ATEC (2832)

## FLUKE

## Fluke 199 Two Channel Scope Meter | 2 Ch, 200 MHz

## **Features**

- > Bandwidth of 200 MHz
- > 2.5 GS/s maximum real-time sample rate
- > 2 Channel Scope Meter
- > Lightweight, handheld device

| Specifications                         |   |           |                |                                      |
|--|---|-----------|----------------|--------------------------------------|
|  | Fluke 199   | Fluke 196 | Fluke 192      | Fluke 123                            |
| Bandwidth                              | 200 MHz   | 100 MHz   | 60 MHz         | 20 MHz                               |
| Max. real-time sample rate             | 2.5 GS/s  | 1 GS/s    | 500 MS/s       | 25 MS/s                              |
| Inputs and digitizers                  | 2 plus external / DMM input   |           |                | 2                                    |
| Independently floating isolated inputs | Up to 1000 V between inputs, references and ground                            |           |                | -                                    |
| Timebase range                         |   |           | ns - 2 min/div | 20 ns - 1 min/div                    |
| Input sensitivity                      | 5 mV-100 V/div  |           |                | 5 mV-500 V/div                       |
| Trigger types                          | Connect-and-View™, free run, single shot,                                     |           |                | Connect-and-View™                    |
|  | edge, delay, video, selectable pulse width and external                       |           |                | free run, single shot<br>edge, video |
| Glitch capture                         | 50 ns   |           |                | 40 ns                                |
| Cursors and Zoom                       | Yes   |           |                |                                      |
| Scope measurements                     | 7 cursor + 24 automatic   |           |                | 26 automatic                         |
| Maximum record length                  | 27,500 pts per input in ScopeRecord mode<br>1,000 pts per input in Scope mode |           |                | 512 min/max pts<br>per input         |
| Capture last 100 screens               | Automatic with Replay capability  |           |                |                                      |
| Dual input TrendPlot                   | Yes with Cursors and Zoom   |           |                | Yes                                  |
| Memory for screens/set-ups             | 10 screens and setups   |           |                | 2 screens, 10 setups                 |
| Memory for recordings                  | Two, each can store 100 scope screens,<br>a ScopeRecord, or a TrendPlot       |           |                |                                      |
| True RMS multimeter                    | 5,000 counts, volts, amps, ohms, continuity, diode, temp                      |           |                |                                      |
| Line power                             | Adapter/battery-charger included  |           |                |                                      |
| Battery power                          | 4 hr NiMH   |           |                | 5 hr NiCad                           |
| Size                                   | 256x169x64 mm   |           |                | 232x115x50 mm                        |
|  | (10.1 x 6.6 x 2.5 in)   |           |                | (2 x 4.5 x 9.1 in)                   |
| Weight                                 | 1.95 kg (4.3 lb)  |           |                | 1.2 kg (2.5 lb)                      |
| Safety certified (EN61010-1)           | 1,000V CAT II/600V CAT III  |           |                | 600V CAT III                         |
| PC and Printer Interface               | With optional optically isolated adapter/cable                                |           |                |                                      |
| Warranty                               | 3 years   |           |                |                                      |



Fluke. Keeping your world up and running.

Fluke Corporation

P.O. Box 9090, Everett, WA 98206

Fluke Europe B.V.

5602 BD Eindhoven, The Netherlands

For more information call: In the U.S.A. (800) 443-5853 or Fax (425) 356-5116 Europe/M-East/Africa +31 (0)40 2 678 200 or Fax +31 (0)40 2 678 222 Canada (800) 36-FLUKE or Fax (905) 890-6866 Other countries +1(425) 356-5500 or Fax +1 (425) 356-5116 Web access: http://www.fluke.com

©Copyright 1999 Fluke Corporation. All rights reserved. Trademarks are the property of their respective owners. Printed in the U.S.A. 7/99 1277204 B-ENG-N Rev A