

## Deep-well compact baths



- 457 mm (18 in) of depth with just 15.9 liters (4.2 gal) of fluid
- Perfect for liquid-in-glass thermometers with optional LIG kit
- Fast, quiet, compact (yet deep!), and economical

Need a bath with a lot of immersion depth, great stability, and a low price tag? How about one that minimizes fluid costs, changes temperatures quickly, and runs quietly?

Hart's new Deep-Well Compact Bath series features four models covering temperatures from  $-80\text{ }^{\circ}\text{C}$  to  $300\text{ }^{\circ}\text{C}$ .

Each model includes a 457 mm (18-inch) deep tank to accommodate long-stem PRTs, SPRTs, and liquid-in-glass (LIG) thermometers. Access openings are 120 by 172 mm (4.7 in by 6.8 in) so you can calibrate many thermometers simultaneously. Yet only 15.9 liters (4.2 gallons) of fluid are needed to get all the benefits Deep-Well Compact Baths offer.

Using Hart's own best-in-class temperature controller, these baths deliver the performance you need for confidence in your calibrations. The 7381 ( $-80\text{ }^{\circ}\text{C}$  to  $110\text{ }^{\circ}\text{C}$ ) features both stability and uniformity better

than  $\pm 0.007\text{ }^{\circ}\text{C}$  over its entire range. The 7341 and 7321 ( $-45\text{ }^{\circ}\text{C}$  to  $150\text{ }^{\circ}\text{C}$  and  $-20\text{ }^{\circ}\text{C}$  to  $150\text{ }^{\circ}\text{C}$ , respectively) are stable to  $\pm 0.005\text{ }^{\circ}\text{C}$  and uniform to  $\pm 0.007\text{ }^{\circ}\text{C}$  at temperatures below ambient. And finally, the 6331 provides stability and uniformity from  $\pm 0.007\text{ }^{\circ}\text{C}$  to  $\pm 0.025\text{ }^{\circ}\text{C}$  over its range from  $40\text{ }^{\circ}\text{C}$  to  $300\text{ }^{\circ}\text{C}$ .

Be sure to understand the performance of the temperature calibration equipment you buy. Some manufacturers offer only limited (and often difficult to interpret) specifications. The table at right includes stability and uniformity values for the entire range of each bath—and tells you what fluid we used in the measurements. If that's still not enough, give us a call and we'll be happy to explain anything—and share data with you.

Hart's control system automatically adds refrigeration when you need to cool down quickly, and shuts down

refrigeration when you need to heat up quickly. For maximum stability, refrigeration levels are automatically balanced to match the set-point temperature you're working at.

Connect any of these baths to a Hart thermometer readout and Hart's industry-leading MET/TEMP II temperature calibration software, and you'll be performing automated probe calibrations within minutes from switch-on.

Want to optimize your bath for calibrating liquid-in-glass thermometers? Simple. With the optional LIG Thermometer Calibration Kit, you get an easy-to-install fluid level adapter tube that raises the meniscus of the bath fluid to within about 12 mm (0.5 in) of the top surface of the bath itself. The kit also includes a thermometer carousel that fits onto the top of the fluid level adapter tube and holds up to ten LIG thermometers in place. A magnifying scope (8X) is also available that mounts to the front of any Deep-Well Compact Bath so you can clearly see the liquid level of your thermometer against its temperature scale.

Like all Hart baths, these units come with a report of test that includes one hour of stability data and a verification of set-point accuracy. A convenient overflow reservoir captures any excess fluid resulting from fluid expansion, allowing the trapped fluid to be reused following subsequent fluid contraction. A drain is also provided for easily emptying the bath's tank when needed.



*The 2019-DCB Liquid-in-Glass Thermometer Calibration Kit includes a carousel which holds up to 10 thermometers and an adapter tube which raises the bath fluid level to within 5–15 mm of the thermometers' readings. The 2069 Magnifier Scope mounts easily to the front of any Deep-Well Compact Bath to provide magnification of 8X or greater.*

# Deep-well compact baths

Specifications	6331	7321	7341	7381
<b>Range</b>	35 °C to 300 °C	-20 °C to 150 °C	-45 °C to 150 °C	-80 °C to 110 °C
<b>Stability</b>	± 0.007 °C at 100 °C (oil 5012) ± 0.010 °C at 200 °C (oil 5017) ± 0.015 °C at 300 °C (oil 5017)	± 0.005°C at -20°C (ethanol) ± 0.005°C at 25°C (water) ± 0.007°C at 150°C (oil 5012)	± 0.005°C at -45°C (ethanol) ± 0.005°C at 25°C (water) ± 0.007°C at 150°C (oil 5012)	± 0.006°C at -80°C (ethanol) ± 0.005°C at 0°C (ethanol) ± 0.005°C at 100°C (oil 5012)
<b>Uniformity</b>	± 0.007 °C at 100 °C (oil 5012) ± 0.017 °C at 200 °C (oil 5017) ± 0.025 °C at 300 °C (oil 5017)	± 0.007 °C at -20 °C (ethanol) ± 0.007 °C at 25 °C (water) ± 0.010°C at 150 °C (oil 5012)	± 0.007 °C at -45 °C (ethanol) ± 0.007 °C at 25 °C (water) ± 0.010 °C at 150 °C (oil 5012)	± 0.007 °C at -80 °C (ethanol) ± 0.007 °C at 0 °C (ethanol) ± 0.007 °C at 100 °C (oil 5012)
<b>Heating Time<sup>†</sup></b>	130 minutes, from 40 °C to 300 °C (oil 5017)	120 minutes, from 25 °C to 150 °C (oil 5012)	120 minutes, from 25 °C to 150 °C (oil 5012)	60 minutes, from 25 °C to 100 °C (oil 5012)
<b>Cooling Time<sup>†</sup></b>	14 hours, from 300 °C to 100 °C (oil 5017)	110 minutes, from 25 °C to -20 °C (ethanol)	130 minutes, from 25°C to -45°C (ethanol)	210 minutes, from 25 °C to -80 °C (ethanol)
<b>Stabilization Time</b>	15–20 minutes			
<b>Temperature Setting</b>	Digital display with push-button data entry			
<b>Set-Point Resolution</b>	0.01 °; 0.00018 ° in high-resolution mode			
<b>Display Resolution</b>	0.01 °			
<b>Digital Setting Accuracy</b>	± 1 °C			
<b>Digital Setting Repeatability</b>	± 0.01 °C			
<b>Access Opening</b>	120 x 172 mm (4.7 x 6.8 in)			
<b>Depth</b>	457 mm (18 in) without Liquid-in-Glass Thermometer Cal Kit 482 mm (19 in) with Liquid-in-Glass Thermometer Cal Kit			
<b>Wetted Parts</b>	304 stainless steel			
<b>Power<sup>†</sup></b>	115 V ac (± 10 %), 50/60 Hz, 14.8 A or 230 V ac (± 10 %), 50/60 Hz, 7.4 A, specify	115 V ac (± 10 %), 60 Hz, 14 A or 230 V ac (± 10 %), 50 Hz, 7 A, specify	115 V ac (± 10 %), 60 Hz, 16 A or 230 V ac (± 10 %), 50 Hz, 8 A, specify	230 V ac (± 10 %), 50 or 60 Hz, specify, 10 A
<b>Volume</b>	15.9 liters (4.2 gal)			
<b>Size (HxWxD)</b>	1067 x 356 x 788 mm (940 mm from floor to tank access opening) [42 x 14 x 31 in (37 in from floor to tank access opening)]			
<b>Weight</b>	41 kg (90 lb)	62 kg (137 lb)	68 kg (150 lb)	91 kg (200 lb)
<b>Automation Package</b>	Interface- <i>it</i> software and RS-232 included (IEEE-488 optional)			

<sup>†</sup>Rated at nominal 115 V (or optional 230 V)

## Ordering Information

<b>6331</b>	Deep-Well Compact Bath, 40 °C to 300 °C	<b>2019-DCB</b>	Liquid-in-Glass Thermometer Calibration Kit (includes bath adapter tube and thermometer carousel)
<b>7321</b>	Deep-Well Compact Bath, -20 °C to 150 °C	<b>2069</b>	8X Magnifier Scope, with mounts
<b>7341</b>	Deep-Well Compact Bath, -45 °C to 150 °C	<b>2001-IEEE</b>	IEEE-488 Interface
<b>7381</b>	Deep-Well Compact Bath, -80 °C to 110 °C	<b>2027-DCBW</b>	TPW Holding Fixture (7321, 7341, 7381)
<b>2012-DCB</b>	Spare Access Cover, Plastic, 7321, 7341, 7381	<b>2027-DCBM</b>	Mercury TP Holding Fixture (7341)
<b>2020-6331</b>	Spare Access Cover, Stainless Steel, 6331		