



A NEW GENERATION

HVA30 - 4 in 1 Universal High Voltage Test System

It is well known that DC "proof" (or hipot) testing of aged extruded cable such as XLPE and EPR is potentially damaging to the cable insulation, causing premature failure of the cable under service conditions. Space charges that develop during DC testing present potential safety hazards to operators and may damage the cable or attached equipment if not discharged correctly.

In addition, DC testing has been found to be ineffective in detecting all but the most serious defects in cables.

Acceptance or maintenance hipot/proof testing using VLF high voltage sinusoidal AC allows the operator to efficiently detect serious cable insulation defects, before they result in an in-service failure, without affecting those healthy sections of the cable that still have remaining service life.

Sinusoidal VLF testing can support effective dielectric diagnostic measurements that are not possible with DC voltages.

- **30 kV • VLF • DC • Jacket/Sheath • Fault Conditioning**

SAFETY FEATURES

- Short circuit protected
- 50Hz 12kV feedback protection
- Status display of all important safety functions and messages
- Safe, easy to use operation with emergency off and key switch lock-out
- Fully integrated discharged circuit to safely ground the DUT (Device Under Test) after testing
- Zero start interlock
- Zero voltage switching



OPERATIONAL FEATURES

- The smallest, lightest, most advanced universal high voltage test instrument available, ideally suited for a variety of applications.
- VLF (0.1Hz), DC (\pm), Cable Fault Conditioning (Burning), and Sheath/Jacket Testing modes all included.
- VLF: the proven and accepted replacement for the traditional DC Hipot or "proof" test for solid dielectric cables such as XLPE and EPR.
- Fully automatic or manual cable test sequences complying with International Standards/Guides such as IEEE 400.2, VDE 0276, CENELEC, HD620 S1, NEN 3620, SANS 10198 and IEC 60060-3.
- Meets all your cable testing requirements.
- True symmetrical sinusoidal, load independent, output waveform across the full load range.
- Real-time Display of actual output wave form.
- Easy to use, ergonomic, menu guided, large backlit user interface.
- Rugged, one piece portability.
- Large output load capability (up to 12 μ F)
- Automatic and integrated load capacitance measurement with optimum frequency selection.
- Storage of test results for later retrieval or download to a PC/Laptop.
- No oil or arcing contacts that require routine maintenance.
- Short circuit protected with active arc management regulation that avoids the tripping of conventional HV test equipment when a dielectric failure occurs.

APPLICATIONS

- Cables: XLPE, PE, EPR, PILC etc.
- Rotating Machines (IEEE 433)
- Capacitors
- Insulators
- Switchgear
- Bushings
- Transformers

DESIGN

The HVA30 is the most advanced HV test system available, it is also the lightest, most compact instrument of its type on the

market. The HVA30 has the highest power to weight ratio of any comparable unit available.

- There is no need to carry two pieces of equipment around and then interconnect them!
- Apart from the variable frequency VLF output, the operator can also select dual polarity DC and cable jacket or sheath testing output modes.
- The applied test voltage, current, capacitance, resistance and time are displayed and recorded.
- The instrument is easily programmable allowing the operator to setup or select test sequences in either automatic or manual mode.
- The HVA30 is capable of testing 0.5µF (Approx. 1500m / 5,000ft of cable) at 0.1Hz and 23kV rms. The frequency of the output can also be reduced allowing even larger capacitance

loads to be tested. At 0.02Hz, approx. 7620m / 25,000ft of cable can be tested.

- To assist the operator, the instrument will automatically calculate the optimum frequency to be selected for larger loads.
- The load independent, symmetrical output waveform avoids the potentially destructive space charge effects caused by DC polarization that occurs in aged extruded cables such as XLPE / PE / EPR, causing them to fail prematurely when exposed to conventional high voltage DC or from a test instrument with large non-symmetrical output waveforms.
- Should a breakdown occur during testing, the actual voltage at which it occurred is displayed and recorded. If cable burning (fault conditioning) mode is activated, the fault resistance can be conditioned to allow easier and less stressful fault location techniques to be applied.
- The results are stored in the instrument's onboard memory allowing easy retrieval and download to a PC or USB drive.

TECHNICAL DATA

Input Voltage	110-230 V 50 / 60 Hz (400 VA)
Output Voltage	Sinusoidal: 0-33 kV peak, symmetrical, 23kV rms DC: ± 0-30 kV Squarewave: 30kV Accuracy: ± 1%; resolution: 0,1kV
Output Current	0-15mA (resolution 1µA), accuracy: ± 1 %
Resistance Range	0.1 MΩ5 GΩ
Output Frequency	0.01....0.1 Hz in steps of 0.01 Hz (default 0.1Hz) – auto frequency selection
Output Load	0.5µF @ 0.1Hz @ 23kV RMS (Approx 1,500m / 5,000ft of cable)* 1.0µF @ 0.05Hz @ 23kV RMS (Approx 3,000m / 10,000ft of cable)* 2.5µF @ 0.02Hz @ 23kV RMS (Approx 8,000m / 25,000ft of cable)* 12.0µF maximum Capacitance * Based on a typical cable: 100pF/ft or 300pF/m
Output Modes	AC (VLF) symmetrical and load independent across full range DC (positive or negative polarity) Burn / Fault Condition or Fault Trip Mode Jacket / Sheath Testing
Protection	50 and 60Hz and RMS Voltage 12kV feedback protection Input surge arrestors (use only voltage regulated generators)
Memory	50 test records stored in non-volatile built in memory
Metering	Voltage and Current (True RMS and/or peak), Capacitance, Resistance, Time, Flashover Voltage
Duty	Continuous - no thermal limitation for operating time.
HV Cable	4.5m (15') with Alligator clamps on end (other options available on request)
Computer Interface	RS232 connection (Software Included), USB Flash Drive
Temperature	Storage: -25°C to +70°C Operating: -5°C to +45°C
Dimensions (LxWxH)	430 x 250 x 360mm
Weight	19.5 kg

ORDER CODES

PRODUCT DESCRIPTION	PART NO.
*Standard HVA30	SH 0201
OPTIONAL ADD-ONS	
TD 30 Tan Delta measurement system	SH 0207
PD 30 Partial Discharge system	SH 0220
Transport case	VKR 0002
Protective cover set	GH 0505
Vacuum bottle test firmware upgrade (DC)	GH 0601
Discharge stick 60kV 1440R 9kJ	GH 0604
Special leads available in various voltages, lengths, and connectors	GH 0501/2/3/4 and GH 0506/20/21

*STANDARD DELIVERY INCLUDES:

- HVA30 Test System
- 4.5m HV cable
- Earth cable
- USB memory stick
- HVA Control Centre Software
- Operating manual

GLOBAL THINKING, LOCAL ACTION

