



Advanced Test Equipment Rentals

www.atecorp.com 800-404-ATEC (2832)

- MO (Mobile Originated) and MT (Mobile Terminated) calls
- SAT and ST frequency error and deviation
- ST duration
- Receiver sensitivity in either 12 dB or 20 dB SINAD
- Forward and Reverse voice modulation
- DTMF tests of the handset
- RF frequency error
- All eight of the phone's RF power levels
- Plots of transmitter and receiver performance over all the phone's operating channels

Digital TDMA (ANSI-136) Testing

To simplify testing, digital phone tests mirror analog test procedures with alterations only to account for the different digital measurements and enhanced features available with modern TDMA (ANSI-136) handsets. Setup and testing of ANSI-136 handsets can be fully automatic for all modes available in the handset, or it can be manual and interactive for diagnostic analysis. In addition to the normal registration and call control functions the 2959 provides control over specialized TDMA (ANSI-136) test features.

- All eleven RF power levels
- TDMA-specific call control such as time slot changes
- DTMF signaling from the handset
- RMS EVM (Error Vector Magnitude), phase error, droop and I/Q origin offset (Carrier leak)
- RMS EVM over the first 10 symbols
- Voice loopback tests or actual voice checks with built-in VSELP and ACELP codecs including the energy (r0) variable of the VSELP codec
- BER verification of the phone's receiver
- MAHO RSSI (Mobile Assisted Handoff-Receive Signal Strength Indication) on the alternate channel at -75, -85 and -95 dBm
- Full-featured Constellation display of the transmitter's modulation

New CDPD Testing Functions

Though some handsets may have CDPD modems built in, they always operate separately from the phone and are tested as autonomous devices. The external modems have an RF connector for their antennas and can be either a PCMCIA device or incorporate a separate connector for serial connection to the computer. Modems can also be integrated directly into laptops, cellular phones and PDAs (Personal Digital Assistants).

Testing CDPD mobile data devices is easy with the 2959's recently upgraded CDPD tests. By installing the modem software, connecting it to the computer and connecting the device's RF antenna connection, the 2959 can perform automated or manual tests of the modem.

By stimulating the CDPD base station messaging and RF parameters, the 2959 provides full external analysis of the mobile

CDPD modem. This includes the ability to test both the RF characteristics of the GMSK carrier and the associated protocol or signaling that is required to establish a wireless data call. Tests performed include:

- RF Power Plot
- Frequency Error
- Modulation Index
- Receiver Sensitivity
- Verification of CDPD Protocol Functions
- GMSK Eye Pattern
- Hand-Offs
- Burst Analysis

SPECIFICATION

RF SIGNAL GENERATOR

FREQUENCY

Range

869.01 to 893 (Mobile Station Rx frequency range)

Resolution

10 kHz

Accuracy

Same as timebase

INTERNAL FM MODULATION

AMPS Test Tone Frequency

1 kHz

AMPS Data

Manchester encoded

NAMPS Test Tone Frequency

1 kHz

NAMPS DSAT/DST

Codes 0 through 6

EXTERNAL FM MODULATION INPUT

Impedance

2 k Ω nominal

Sensitivity

100 Hz/mV peak, $\pm 30\%$ at 1 kHz

Frequency Range

300 Hz to 3 kHz

$\pi/4$ DQPSK MODULATION

RMS Error Vector Magnitude (EVM)

As defined by EIA/TIA-627

CDPD GMSK MODULATION

Data Rate

19.2 kbps, ± 1 bps

Deviation

4.8 kHz peak, ± 240 Hz

B.T. Product

0.5

RF OUTPUT (T/R CONNECTOR)**Level Range**

-40 to -127 dBm

Level Resolution

0.1 dB

Level Accuracy

± 1.5 dB

RECEIVER**FREQUENCY****Range**

824.01 to 848.97 MHz (Mobile Station Tx Frequency Range)

Resolution

10 kHz

INPUT POWER**Maximum Input**

5 W maximum (continuous into T/R Connector)

SENSITIVITY**FM Audio**

-90 dBm, 12 dB SINAD

METER FUNCTIONS**RF POWER****Frequency Range**

824.01 to 848.97 MHz

Power Range

0.05 mW to 4 W

Accuracy (Reading <3 mW)

$\pm 20\%$, ± 1 digit

Accuracy (Reading ≥ 3 mW)

$\pm 15\%$, ± 1 digit

T/R Port VSWR

<1.5:1

RF FREQUENCY ERROR**Range**

± 10 kHz

Resolution (N/AMPS, TDMA)

1 Hz

Resolution (CDPD)

10 Hz

Accuracy

Same as timebase, ± 2 Hz

ANTENNA VSWR MEASUREMENT**Range**

1.20:1 to 4.00:1

Resolution

0.01

AF COUNTER**SAT Range (AMPS)**

5,950 Hz to 6,050 Hz

ST Range (AMPS)

9,950 Hz to 10,050 Hz

Resolution

1 Hz

Accuracy

± 1 Hz, ± 1 digit

FREQUENCY DEVIATION

	Minimum		Maximum
SAT Range (AMPS)	± 1 kHz	to	± 3 kHz
ST Range	± 7 kHz	to	± 9 kHz
DSAT/DST Range	± 0.5 kHz	to	± 0.9 kHz
AMPS Voice Range	± 1 kHz	to	± 14 kHz
NAMPS Voice Range	± 1 kHz	to	± 4 kHz

For CDPD GMSK

± 4.8 kHz (with any valid CDPD data)

Deviation Resolution

0.01 kHz

Deviation Accuracy

$\pm 5\%$, ± 1 digit

SINAD**Range**

3 to 40 dB

Resolution

0.1 dB

Accuracy

± 1 dB at 12 dB SINAD

Test Frequency

1 kHz

CABLE LOSS MEASUREMENT**Cable Loss Range**

0.0 to 20.0 dB

Cable Loss Resolution

0.1 dB

Cable Loss Accuracy

± 0.5 dB (0 to 3 dB reading)

 $\pi/4$ DQPSK

(EVM)

EVM Range

0% to 23% RMS

EVM Resolution

0.01%

EVM Error

<1.7% RMS

TIMEBASE

INTERNAL TIMEBASE

Frequency

10 MHz nominal

Uncertainty

±0.1 ppm

Temperature Stability

±0.1 ppm

Ageing Rate

±0.1 ppm/year

EXTERNAL TIMEBASE

Level

0.25 to 6.0 V p-p

Frequency

10 MHz

Impedance

1 kΩ nominal

POWER REQUIREMENTS

AC INPUT

Source Voltage

100 to 240 VAC

Source Frequency

47 Hz to 63 Hz

Power Consumption

<75 W

DC INPUT

Source Voltage

11.5 to 15 VDC

Power Consumption

<75 W

PHYSICAL CHARACTERISTICS

DIMENSIONS AND WEIGHT

Outside Dimensions (H x W x D)

164.9 mm x 303.6 mm x 381.5 mm

6.43 in. x 11.84 in. x 14.88 in.

Weight

11.8 kg (not including lid or lid contents)

26 lbs. (not including lid or lid contents)

VERSIONS AND ACCESSORIES

When ordering please quote the full ordering number information.

Ordering Numbers

Versions

2959 Advanced Multi-Mode Cellular Test Set

2959-C Advanced Multi-Mode Cellular Test Set with Certificate of Calibration

Accessories

AC0350 2959 Operational Manual (Spanish)

AC1081 CDPD Version 1.4 Software Upgrade

AC1082 CDPD Version 1.4 Software Upgrade for Microcell 100

Extended Warranties

W2959/203 Warranty Extension 1 yr (Total Warranty 3 yrs)

W2959/204 Warranty Extension 2 yr (Total Warranty 4 yrs)

W2959/205 Warranty Extension 3 yr (Total Warranty 5 yrs)

CHINA

Tel: [+86] (21) 6282 8001
Fax: [+86] (21) 6282 8002

EUROPE

Tel: [+44] (0) 1438 742200
Fax: [+44] (0) 1438 727601

FRANCE

Tel: [+33] 1 60 79 96 00
Fax: [+33] 1 60 77 69 22

HONG KONG

Tel: [+852] 2832 7988
Fax: [+852] 2834 5364

SCANDINAVIA

Tel: [+45] 9614 0045
Fax: [+45] 9614 0047

SPAIN

Tel: [+34] (91) 640 11 34
Fax: [+34] (91) 640 06 40

UNITED KINGDOM

Tel: [+44] (0) 1438 742200
Toll Free: [+44] (0800) 282 388 (UK only)
Fax: [+44] (0) 1438 727601

USA

Tel: [+1] (316) 522 4981
Toll Free: [+1] (800) 835 2352 (US only)
Fax: [+1] (316) 522 1360



As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2003.

www.aeroflex.com
info-test@eroflex.com



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.

Part No. 46891/020, Issue 4, 11/03