



## MAGIO MS-1000F Refrigerated / Heating circulator

As with all circulators from the MAGIO range, the refrigerated circulators stand out thanks to their premium quality, high performance and intuitive operation. The devices offer extra strong pressure and suction pumps, thus fulfilling the highest demands for temperature control of external applications. Whether in basic research, material testing or technical systems – the MAGIO refrigerated circulators offer high-tech solutions for high customer requirements.

### High resolution TFT touch display

The modern TFT touch display gives you all the important information at a glance. Three large, predefined main screens clearly display data and graphics with various application priorities. Menu navigation is self-explanatory, arranged by relevance to daily operations and easy to operate with the touch of a finger. The in-built help function provides detailed support in case of additional questions.



### Your advantages

- USB connection
- Class III (FL) according to DIN 12876-1
- RS232 interface for online communication
- Integrated programmer
- Integrated external Pt100 connection
- Ethernet
- analog interfaces (accessory)
- Ideal for demanding external applications
- Simple control of complex applications
- Flow rate 16 ... 31 l / min, pressure 0.24 ... 0.92 bar, suction 0.03 ... 0.4 bar
- Continuously adjustable, extremely powerful pressure / suction pump
- Large, high-resolution TFT touch display with multilingual user interface
- Parts being in contact with the medium made of stainless steel
- Profibus DP (Accessory)
- Modbus

### Technical data

<b>Available voltage versions</b>		<b>Bath</b>	
Order No.	9 032 707	Bath tank	Stainless steel
Available voltage versions:		Bath cover	integrated
9 032 707.02		Usable bath opening in. (W x L / D)	7.1 x 5.1 / 5.9
9 032 707.05			
9 032 707.04			
9 032 707.33			
9 032 707.33.chn			
<b>Cooling</b>		<b>Other</b>	
Cooling of compressor	1-stage Air	Classification	Classification III (FL)
		IP Code	IP 21
		Pump function	Pressure Suction Pump
		Pump type	Immersion Pump
<b>Electronics</b>		<b>Dimensions and volumes</b>	
External pt100 sensor connection	integrated	Weight lbs	119.3
Integrated programmer	8x60 steps	Dimensions in. (W x L x H)	16.5 x 19.3 x 27.6

Temperature control	ICC	Filling volume l	5 ... 7.5
Absolute temperature calibration	3 Point Calibration	Pump connections	M16x1 male
Temperature display	Temperature display		
7" TFT Touchscreen			
Temperature setting	Temperature setting		
Touchscreen			
Electronic Timer hr:min	00:00 ... 00:00		

**Temperature values**

Setting the resolution of the temperature display °C	0.01
Working temperature range °C	-50 ... +200.0
Temperature stability °C	+/-0.01
Ambient temperature °C	+10.0 ... +40.0
Temperature display resolution °C	0.01

**Performance values**

115V/60Hz (Nema N5-20 Plug)

**115V/60Hz**

Heating capacity kW	1							
Cooling capacity (Ethanol)								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -5.8							

200-230V/50-60Hz (CH Plug Type SEV 1011)

**200V/50Hz**

Heating capacity kW	1.6							
Cooling capacity (Ethanol)								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -5.8							

**200V/60Hz**

Heating capacity kW	1.6							
Cooling capacity (Ethanol)								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -5.8							

**230V/50Hz**

Heating capacity kW 2

**Cooling capacity (Ethanol)**

°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11

Viscosity max. cST 50

Refrigerant R449A

Filling volume g 190

Global Warming Potential for R449A 1397

Carbon dioxide equivalent t 0.265

Pump capacity flow rate l/min 16 ... 31

Pump capacity flow pressure psi 3.5 ... 13.3

Maximum suction psi -0.4 ... -5.8

**230V/60Hz**

Heating capacity kW 2

**Cooling capacity (Ethanol)**

°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11

Viscosity max. cST 50

Refrigerant R449A

Filling volume g 190

Global Warming Potential for R449A 1397

Carbon dioxide equivalent t 0.265

Pump capacity flow rate l/min 16 ... 31

Pump capacity flow pressure psi 3.5 ... 13.3

Maximum suction psi -0.4 ... -5.8

200-230V/50-60Hz (UK Plug Type BS1363A)

200V/50Hz								
Heating capacity kW	1.6							
Cooling capacity								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -5.8							

200V/60Hz								
Heating capacity kW	1.6							
Cooling capacity (Ethanol)								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -5.8							

230V/50Hz								
Heating capacity kW	2							
Cooling capacity (Ethanol)								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -5.8							

230V/60Hz								
Heating capacity kW	2							
Cooling capacity (Ethanol)								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -5.8							

200-230V/50-60Hz (Schuko Plug - CEE 7/4 Plug Type F)

200V/50Hz								
Heating capacity kW	1.6							
Cooling capacity (Ethanol)								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -0.6							

200V/60Hz								
Heating capacity kW	1.6							
Cooling capacity (Ethanol)								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -5.8							

230V/50Hz								
Heating capacity kW	2							

230V/60Hz								
Heating capacity kW	2							

Cooling capacity (Ethanol)								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -5.8							

Cooling capacity (Ethanol)								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -5.8							

200-230V/50-60Hz (CN Plug)

200V/50Hz								
Heating capacity kW	1.6							
Cooling capacity (Ethanol)								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -5.8							

200V/60Hz								
Heating capacity kW	1.6							
Cooling capacity (Ethanol)								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -5.8							

230V/50Hz								
Heating capacity kW	2							
Cooling capacity (Ethanol)								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -5.8							

230V/60Hz								
Heating capacity kW	2							
Cooling capacity (Ethanol)								
°C	200	20	10	0	-10	-20	-30	-40
kW	1	1	0.96	0.96	0.7	0.51	0.25	0.11
Viscosity max. cST	50							
Refrigerant	R449A							
Filling volume g	190							
Global Warming Potential for R449A	1397							
Carbon dioxide equivalent t	0.265							
Pump capacity flow rate l/min	16 ... 31							
Pump capacity flow pressure psi	3.5 ... 13.3							
Maximum suction psi	-0.4 ... -5.8							

All Benefits



**100% Checked.**  
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



**Green technology.**  
Development consistently applied environmentally friendly materials and technologies.



**Intelligent temperature control.**  
Intelligent cascade control - automatic and self-optimizing adaptation of the PID control parameters with external stability of +/- 0.05 °C.



**JULABO. Quality.**  
Highest standards of quality for a long product life.



**Quick start.**  
Individual JULABO consultation and comprehensive manuals at your disposal.




**Satisfied customers.**  
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



**Services 24/7.**  
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at [www.julabo.com](http://www.julabo.com).



**Touch display. Perfect operation.**  
With the touch display, the user always has an overview of all values and functions. The intuitive and multilingual menu structure enables perfect control.



**Many interfaces.**  
Straight-forward remote control, data management, and integration into process structures. USB, Ethernet, RS232, SD card, and alarm off are permanently integrated. Further interfaces available as accessories.



**Maximum safety.**  
Classification III according to DIN12876-1 enables safe operation, even with flammable fluids. Automatic switch-off in the event of high temperature or low liquid level.



**Space saving. Free up space.**  
Place your JULABO Circulator right next to an application, another unit, or wall. That saves space. This is made possible by eliminating vents and connections on the sides.



**Multi-lingual.**  
Operation in multiple languages.



**Programmer. Integrated.**  
The integrated internal programmer makes it possible to automatically run temperature time profiles.



**Temperature. Under control.**  
External Pt100 sensor connection for precise measurement and control directly in the external application.



**Fill level. Monitored.**  
Fill level indicator on the display for heat-transfer liquid.



**Process stability.**  
Early warning - visual and acoustic - of critical states increases process stability.



**Process. Under control.**  
Full control of the dynamic, access to all important control parameters for individual process optimization.



**ATC3. Calibration.**  
'Absolute Temperature Calibration' for compensating a physically caused temperature difference, 3-point calibration.



**Stable. Mobile.**



**Energy-saving.**  
The high-quality insulation of all relevant components saves energy.



**Everything made of stainless steel.**  
Quality and material compatibility at the highest level. All parts in contact with the medium are entirely made of stainless steel.



**Most powerful pump.**  
The integrated pressure/suction pump with performance values of 0.9 bar and -0.5 bar is the most powerful in its class and continuously adjustable.



**Wide range.**  
Refrigerated and heating circulator in various combinations, circulator in various sizes. Maximum flexibility through a large selection of accessories.



**Connection. Easy.**  
Inclined pump connections (M16x1) facilitate the connection of applications. Each unit includes 2 barbed fittings of 8/12 mm diameter each.



**Analog I/O.**  
Analog interfaces for integration into process control systems (optional).



**Condensation protection.**  
Superb design solution. Integrated ventilation directs air over the bath lid and minimizes condensation.