



Advanced Test Equipment Rentals
www.atecorp.com 800-404-ATEC (2832)



....the *Best* just got *Better!*
EZ-RESTORE™ OVERDRIVE



Absolute Lightest Unit
< 48.5 Lbs

Only Unit with
Back-Feed Alert

Only Unit with
SAFE OP Check

Only Unit with
USB  LOAD

Only unit with
Trans-flective TFT
Color LCD

...no adjustments required, just follow the ...



Technical Specifications **EZ-RESTORE™ OVERDRIVE**


SECTIONALIZING



Start Test

Alphanumeric Color Display

SECTIONALIZING



Start Test

Graphic Color Display

Energy / Voltage Output 1,100Joules @ 12kV*
other voltages available, please inquire

DC Hipot Output (optional) 12kV
option includes indication of Breakdown Voltage

Measuring Range: up to 25,000 ft

Sectionalizing Method

Automatic Combination LV -TDR & ARM® to identify, locate & isolate faulted spans**

Fault Distance Accuracy:

< 2.5 feet depending on displayed range

Display Screen:

Trans-reflective 5.7" 640 x 480 TFT Color LCD

Leads / Terminations

15 ft HV cable MC Con. / Hotline Clamp
HV return with Hotline Clamp,
15 ft Ground Cable with Hotline Clamp
Cables are stored in inside cable tray
optional up to 50' cables available

Dimensions: 19.7 x 12 x 18

Weight: 48.5 lbs

* Typical life expectancy 5,000 discharges

Convenience Features:

- Computer controlled automatic sectionalizing and fault locating process
- Unit is operated via rotary "TURN & CLICK"
- Adjustment of Transformer *Detection Sensitivity*

Safety Features:

- Operator always in full control of HV output
- "Emergency Off" Red Mushroom button
- Auto "Time out" discharges and grounds
- Back-Feed Recognition (Optional)
- SAFE OP feature checks Ground Connections

Power Supply:

- Internal** 12V Battery 12 AH
- **External** 12VDC / 120VAC

Outdoor Suitability

- Rugged design, weather proof
- High impact resistant Pelican Roll / Carrying Case
- Stainless Steel / Brass hardware

Operating Temperature:

- 5 F to 105 F (-20 °C + 40 °C)

Options

- Optional Elbow Adapter available, 15 / 25 / 35 kV

Your Local Representative is:

HDW Electronics Inc., 89 S. Commerce Way
Bethlehem PA 18017

Tel: (610) 861-8862 • Fax: (610) 861-8864

Internet: www.hdwelectronics.com

E-mail: sales@hdwelectronics.com

**Patent No. US 6, 683,459 B2

ARM® is a Trademark of HDW Electronics, Inc.

EZ-RESTORE® is a Trademark by HDW . Electronics, Inc