

# MS•60

## High sensitivity portable helium leak detector -Now with Touch Screen Graphical User Interface

**Quickly and accurately detects leaks for a broad range of applications**

- The Touch-Screen GUI allows for greater system control and monitoring during system start-up and operation.
- Displays include system status, accept/reject status, system health, setup, calibration and other diagnostic functions.
- Standard 7 cfm direct drive foreline/roughing pump for faster cycle times; optional 10.6 cfm available
- Internal or external calibration for flexibility
- Digital Input/Digital Output
- Fully automatic
- Dual magnetic sector high resolution mass spectrometer
- Three modes of operation



### Applications

- Automotive
- Compressors
- Electron Beam –Welders
- Gas Tanks
- Heat Exchangers
- High Pressure -Devices
- Nuclear Reactors
- Power Distribution Plants
- Refrigeration Parts

### Features:

- ▶  $5 \times 10^{-12}$  atm-cc/sec sensitivity
- ▶ Two Lanthanum/Yttrium filaments
- ▶ Password security
- ▶ AZ<sup>3</sup>, 3 modes of advanced auto-zero

### Benefits:

- ▶ Most sensitive portable available
- ▶ For longer service life
- ▶ Protects against tampering
- ▶ Faster, more accurate testing



**Vacuum Instrument Corporation**

2099 Ninth Avenue • Ronkonkoma, NY 11779 • T 631 737 0900 • F 631 737 1541 • sales@vicleakdetection.com

[www.vicleakdetection.com](http://www.vicleakdetection.com)



## MS•60 PERFORMANCE SPECIFICATIONS

Characteristics	Units	7 CFM	10.6 CFM
Sensitivity, vacuum *	atm-cc/sec	$5.0 \times 10^{-12}$	
Sensitivity, sniffing		$1.0 \times 10^{-8}$	
Leak Measurement Range		$5.0 \times 10^{-12}$ to $1.0 \times 10^{-4}$ (10 w/ext pump)	
Leak Ranging	-	Auto/Manual	
Start-up time	minutes	<3	
Response Time *	seconds	<2 direct	
Resolution for <sup>4</sup> He *	-	14	
Mass Spectrometer Tube	-	180° deflection; dual-magnetic sector	
Auto-tuning	-	Yes	
Auto-calibration	-	Internal – yes; External - manual	
Auto-zeroing	-	Yes, 3 modes: Normal, Spray and Hold	
Reject set-point	-	Yes	
Built-in calibrated leak	-	Yes	
NIST traceable	-	Yes	
Temperature compensated	-	Yes	
He Scan	-	Yes	
Filaments	-	2 - Lanthanum/Yttrium	
Maximum Operating Pressure	Torr	7.5, 760 w/ext roughing option	
Display	-	Alpha/Numeric	
Units	-	atm cc/s, mbar*I/s, Pa*M <sup>3</sup> /sec	
I/O	-	0-5V or 0-10V chart; Linear Mantissa and Exponent or Logarithmic LR and Port Pressure and Foreline Pressure	
Digital I/O (PLC interface)	-	6-output, 7-input	
Printer Port	-	Yes	
RS-232C	-	Yes	
Software	-	Password security, 3-mode auto-zero	
<b>VACUUM SYSTEM</b>			
Vacuum Mode	-	Direct, reverse or combination flow	
Roughing Pump	cfm	7 rotary vane	10.6 rotary vane
High Vacuum Pump	liters/second	61 turbomolecular	
Vacuum Gauging	-	Pirani: Test port & foreline; Ion: High vacuum	
Test Port Connection	-	NW25	
<b>PHYSICAL</b>			
Dimensions (W x H x D)	Inches (cm)	21 x 16.9 x 16.5 (53.3 x 42.9 x 41.9)	
Weight	lbs. (kg)	133 (60.3)	135 (61.2)
<b>ELECTRICAL</b>			
Power	V/Hz/A	115/50-60/8; 230-240/50-60/5; 100/50-60/8	

### Vacuum Instrument Corporation

2099 Ninth Avenue • Ronkonkoma NY 11779 • Tel 631 737 0900 • Fax 631 737 1541

www.vicleakdetection.com • email sales@vicleakdetection.com

REV090210

\* Performance determined in accordance with American Vacuum Society Standards; Specifications subject to change without notice.

©2009 Vacuum Instrument Corporation; ©VIC Leak Detection is a registered trademark and the VIC symbol and the MS-(series) are trademarks of Vacuum Instrument Corporation.