

Advanced Test Equipment Corp. www.atecorp.com 800-404-ATEC (2832)





→ ProductInformation

- Intelligent data logging system that only logs data when in a field, at 1 second intervals, to maximize storage
- Frequency range of operation:
 50 MHz 60 GHz
- Frequency response: Shaped (Occupational/Controlled)
- Sensor polarization: Isotropic
- RF Fields measured: Magnetic (H-fields) close to the antenna and Electric (E-fields) far from the source
- Calibration interval: 2 year
- Battery life: 6-12 months on average usage
- Dimensions: 5.8 x 1 x 1.7 inches (146 x 26 x 42 mm)
- Measures in accordance with ICNIRP (1998 & 2020)
 FCC (NCRP) OET65 (1997)
 Canada Safety Code 6 (2015)



What's in the box?

The all-weather IP64 rated fieldSENSE60 comes encased in a compact, zipper case with a shock proof polyurethane custom-moulded inner that ensures device protection during transit or in storage.

- harness attachment mechanism
- clip mechanism
- rubber strap mechanism
- coiled lanyard system
- USB connectivity for data logging and time sync
- · comprehensive user manual
- spare alkaline batteries







WORKS AS HARD AS YOU

www.fieldsense.com info@fieldsense.com