

# Advanced Test Equipment Corp. www.atecorp.com 800-404-ATEC (2832)

**CONFIGURATION GUIDE** 

# N5186A MXG Vector Signal Generator

## Introduction

This configuration guide contains information to help you configure your N5186A MXG vector signal generator to meet your requirements. Ordering optional capabilities at the time of purchase provides the lowest overall cost of ownership.



# **Configure Hardware**

### Select number of channels

Configuration	Required options	Descriptions	Additional information
One channel	N5186A-001	Add channel one	Required for all configurations
Four channels	N5186A-001	Add channel one	
	N5186A-002	Add channel two	
	N5186A-003	Add channel three	
	N5186A-004	Add channel four	

# **Select connector configuration**

Option	Description	Additional information
N5186A-1EM	Move all connectors to rear panel	

# Select channel features (ordered once per channel)

Option	Description	Additional information
Frequency opti	ons (must select one; option will be duplicated on all channels)	
N5186A-503	Frequency range, 9 kHz to 3 GHz	
N5186A-506	Frequency range, 9 kHz to 6 GHz	
N5186A-508	Frequency range, 9 kHz to 8.5 GHz	
Bandwidth opti	ons (must select one; option may be different on each channel)	
N5186A-B2X	RF bandwidth, 250 MHz with 256 MSa	
N5186A-B5X	RF bandwidth, 500 MHz with 256 MSa	
N5186A-B9X	RF bandwidth, 960 MHz with 256 MSa	
Memory option	s (optionally select one; option may be different on each channel)	
N5186A-M05	Baseband generator memory upgrade to 512 MSa	
N5186A-M10	Baseband generator memory upgrade to 1 GSa	
N5186A-M20	Baseband generator memory upgrade to 2 GSa	
Phase noise op	tions (optionally select one; option will be duplicated on all channels)	
N5186A-EP3	Low phase noise	Not compatible with EP4
N5186A-EP4	Enhanced low phase noise	Not compatible with EP3
High output por	wer options (optionally select; option will be duplicated on all channels)	
N5186A-1EA	High output power from 9 kHz to 3, 6, or 8 GHz	
Vector system	eature options (optionally select; option may be different on each chann	el)
N5186A-403	AWGN and CW interferer	



Option	Description	Additional information	
General perforn	General performance feature options (optionally select; options will be duplicated on all channels)		
N5186A-099	Expanded license key upgradability	Option 099 is required for anyone considering future upgrades. Option 099 simplifies the upgrade process by enabling upgrades via a license key for options 1EA, 1EQ, and UNV.	
N5186A-1EQ	Low specified power (< -110 dBm)		
N5186A-UNV	Enhanced dynamic range		
Embedded reflectometer options (optionally select; option will be duplicated on all channels)			
N5186A-V08	Embedded reflectometer from 9 kHz to 3, 6, or 8.5 GHz	E7653APPC is recommended with option V08.	

# **Configure Software**

#### **Included software**

The N5186A MXG base configuration includes the following software tools.

#### Description

·	
Sample waveforms	
PathWave General Purpose Signal Generation	

### **Embedded PathWave software tools**

Embedded PathWave software tools can be used to create and playback waveforms through the MXG touch-optimized graphical user interface. Optionally select any models. One software license per instrument is required.

Model	Description	
E7608APPC	PathWave Signal Generation for custom IQ modulation	
E7621APPC	PathWave Signal Generation for basic multitone	
E7642APPC	PathWave Signal Generation for IQ based AM, FM, phase modulation	
E7653APPC	PathWave automatic channel response correction and S-parameter de-embedding (includes instrument nonlinear correction)	



#### Additional PathWave software tools and MATLAB

These PathWave software tools can be used to create and playback waveforms through file-export based waveform playback. Real-time signal creation is not supported. Only node-locked licenses are available. Optionally select any models. One software license per instrument is required. For additional information, see the PathWave Signal Generation Brochure.

Model	Description	
Cellular communications		
N7600EMBC	PathWave Signal Generation for W-CDMA/HSPA+	
N7601EMBC	PathWave Signal Generation for cdma2000/1xEV-DO	
N7602EMBC	PathWave Signal Generation for GSM/EDGE/Evo	
N7612EMBC	PathWave Signal Generation for TD-SCDMA/HSPA	
N7624EMBC	PathWave Signal Generation for LTE/LTE-Advanced/LTE-A Pro FDD	
N7625EMBC	PathWave Signal Generation for LTE/LTE-Advanced TDD	
N7626EMBC	PathWave Signal Generation for V2X	
N7631EMBC	PathWave Signal Generation for 5G NR	
N7632EMBC	PathWave Signal Generation for NR-V2X	
Wireless connectivity		
N7606EMBC	PathWave Signal Generation for Bluetooth	
N7610EMBC	PathWave Signal Generation for IoT	
N7615EMBC	PathWave Signal Generation for Mobile WiMAX	
N7617EMBC	PathWave Signal Generation for WLAN 802.11	
Audio/video broadcasting		
N7611EMBC	PathWave Signal Generation for broadcast radio	
N7623EMBC	PathWave Signal Generation for digital video	
N7640EMBC	PathWave Signal Generation for LMR	
General RF and Microwave		
N7608EMBC	PathWave Signal Generation for custom modulation	
N6171A	MATLAB software (for standalone PC use)	



#### **Select Accessories**

Model	Description	Additional information
1CM110A	Rackmount flange kit	
1CN106A	Front handle kit	
1CP104A	Rackmount flange and front handle kit	

# **KeysightCare Coverage**

One year of KeysightCare Assured is included with your new N5186A MXG Vector Signal Generator for priority access to technical experts and optimized uptime to mitigate project risk. Multiyear upgrade options to KeysightCare Enhanced add calibration coverage for full performance verification and accelerated turnaround times.

Obtain multi-year KeysightCare upfront to lock in the service pricing of today and operate with a planned spending profile and eliminate the need for yearly requests for maintenance budget. Plus, you benefit from secured service for 2, 3, or 5 years.

Service	Function	
KeysightCare Enhanced <sup>1</sup>	Includes tech support, warranty, and calibration	
R-55B-001-1	KeysightCare Enhanced – Upgrade 1 year	
R-55B-001-2	KeysightCare Enhanced – Extend to 2 years	
R-55B-001-3	KeysightCare Enhanced – Extend to 3 years (Recommended)	
R-55B-001-5	KeysightCare Enhanced – Extend to 5 years (Recommended)	
R-55B-001-3CC	KeysightCare Enhanced – Extend to 3 years (China only) <sup>2</sup>	
R-55B-001-5CJ	KeysightCare Enhanced – Extend to 5 years (Japan only)	
KeysightCare Assured	Includes tech support and warranty	
R-55A-001-2	KeysightCare Assured – Extend to 2 years	
R-55A-001-3	KeysightCare Assured – Extend to 3 years	
R-55A-001-5	KeysightCare Assured – Extend to 5 years	
R-55A-001-3CC	KeysightCare Assured – Extend to 3 years (China only)	
R-55A-001-5CC	KeysightCare Assured – Extend to 5 years (China only)	
R-55A-001-5CJ	KeysightCare Assured – Extend to 5 years (Japan only)	
Start-Up Assistance		
PS-S20	Startup assistance, daily	
PS-X10	Custom Services	

<sup>&</sup>lt;sup>2</sup> Contact Keysight for 5-year coverage.



<sup>1</sup> Available in select countries. R-55B-001-2/3/5 must be ordered with R-55B-001-1. For details, please view the KeysightCare datasheet.