



WPF6 Probe

100 kHz - 6 GHz



- High sensitivity from 0.2 V/m
- Isotropic & True RMS measurement
- Excellent attenuation at 50/60 Hz
- Measurements in accordance with International Standards

100 kHz - 6 GHz

E

RMS

ISOTROPIC



Telecommunications
Certification and audit of telecommunication services (GSM, 3G, LTE, TDT, AM, FM, WiFi, etc.).



Industry
Assessment of industrial processes for worker's exposure protection.



Defence
Assessment of military sites and personnel exposure protection.



Labs/R&D
RF exposure protection of R&D and labs personnel.



Technical Specifications

	WPF6	WPF6-HP High Power version
Frequency range	100 kHz – 6 GHz	
Sensor type	Isotropic RMS diode technology	
Type of frequency response	Flat	
Measurement range	0.2 – 130 V/m (CW) 0.2 – 20 V/m (RMS)	0.2 – 1000 V/m (CW) 0.2 – 20 V/m (RMS)
Dynamic range	56 dB	73 dB
Sensitivity	0.2 V/m	
Resolution	0.02 V/m (until 7.5 V/m) 0.1 V/m (from 7.5 V/m to 130 V/m)	
Frequency response (*)	better than -3 dB @ 100 kHz ±1.5 dB (250 kHz – 5.5 GHz) better than -2 dB (5.5 – 6 GHz)	
Linearity	± 0.5 dB (0.5 V/m – 100 V/m)	
Isotropic deviation	±0.3 dB (1 GHz) ±1 dB (6 GHz)	
Calibration	ISO 17025 Accredited Calibration (ILAC)	
Calibration period	24 months (recommended)	
Temperature range	- 20 °C to 50 °C	
Temperature response	+ 0.1 / - 1 dB (related to 20 °C)	
Dimensions	28.4 cm x 6 cm Ø	
Weight	95 g	
Attenuation at 50/60 Hz	> 80 dB	

(*) The frequency response can be corrected with the SMP2 by using the correction factors stored in the probe (ISO 17025 accredited calibration).

Compatible with **SMP2**, **MonitEM**, **MapEM**

Product specifications and descriptions in this document subject to change without notice.



WPF6_EN_2009_v2.2