



Technical Specifications

SONYKS

Take control. Be your own guide.

Sonyks™ is a major leap in guided wave equipment. Eddyfi Technologies has redefined guided wave ultrasonic testing with Sonyks setting new benchmarks for data quality, versatility, ease of use, and deployment.

THE NEXT GENERATION OF GUIDED WAVE TESTING

From those who pioneered guided wave testing (GWT) commercially, the state-of-the-art system comes with a large high-quality touchscreen, ultra-fast electronics for rapid data acquisition, and on-the-spot data analysis capabilities for accurate reporting. Sonyks has reinvented guided waves, making the technology simpler and more accessible for the industry.

The system offers an unprecedented ability to inspect more piping applications, including piping and tubing, in the most cost and time-efficient manner.

The instrument is also compatible with typical piezo-transducer rings found on the market. Reuse your own rings and make the most of your past investment in guided waves. Couple your existing collars to a new-generation instrument with best-in-class electronics and give a second life to your inspection programs.

Sonyks comes with a large high-quality touchscreen, ultra-fast electronics for rapid data acquisition, and on-the-spot data analysis capabilities for accurate project based reporting. Sonyks has reinvented guided waves, making the technology simpler and more accessible for the industry.






Figure 1: Annotated breakdown of Sonyks instrument.



Figure 2: Annotated breakdown of Sonyks Piezo and Mageto tool.

INCREASING PRODUCTIVITY AND UTILIZATION

Thanks to project-based inspection setup and increased portability, the number of locations inspected per day is increased by 50%.

SIMPLIFIED & STREAMLINED WORKFLOW FOR TOP EFFICIENCY

Thanks to a project-based inspection setup, time spent at a location can be reduced by 33%. This combined with a new multilocation reporting feature generates significant time savings.

COMPREHENSIVE DATA AT YOUR FINGERTIPS

Sonyks is the first instrument with an onboard screen for GWT interpretation. It uses a combination of broadband and Full Matrix Capture (FMC) data collection, meaning that all data ever needed is collected once to make analysis possible anywhere. Move on to the next location knowing you have all the necessary data with increased speed and peace of mind.



Figure 3: Sonyks instrument with the Piezo tool on site.

BEST INSTRUMENT AND TOOLING PROVIDE THE BEST DATA

With an unmatched signal-to-noise ratio (SNR), Sonyks inspects longer distances and locates even smaller defects. This improved SNR can dramatically simplify analysis and increase the overall efficiency of the inspection by 50%.

SOUND EVOLUTION FOR GWT EXPERTS

Reuse transducer rings you already own and make the most of your past investment in GWT. Couple your existing collars to a new-generation instrument with best-in-class electronics and give a second life to your inspection programs.

RAMP UP YOUR UTILIZATION RATE

Sonyks is an incredibly versatile system that allows operators to address more applications thanks to short-range and medium-range capabilities in addition to long-range ultrasonic testing. For example, use the new 128 kHz magnetostrictive collar to inspect flanged pipes efficiently.



Figure 4: Sonyks instrument with the Magneto collar on site.

BENEFITS

- Unmatched SNR for longer inspection runs
- Easy to interpret data making the technology more accessible
- Compatible with other manufacturers transducer rings
- Collect all data needed in one scan for accurate and auditable results
- Streamlined workflow, increasing efficiency and inspection capabilities
- Transducer rings suitable for pipes ranging 1.5in (48.3mm) to 72in (1800mm)
- Internal compressor for inflation of collars



Figure 5: Guided wave 20cm (8in) pipe inspection with Sonyks Piezo tool.

SPECIFICATIONS

INSTRUMENT		
Dimensions (W x H x D)	355 x 288 x 127mm (14.0 x 11.3 x 5.0in)	
Weight (with 1 x battery)	7.2kg (15.9lb)	
Power Requirements	100-240 VAC, 50-60 Hz	
Power Supply	Direct VAC or onboard batteries	
Batteries	Type	10.8 V Li-ion, rechargeable, DOT compliant
	Typical Life	6-8 hours
Video Output	HDMI	
Number of Channels Transmit	40	
Transmitter Frequency Range	5-260 kHz	
Standard Output Voltage	200V, peak to peak	
Number of Channels Receive	40	
Receiving Gain Range	Up to 100 dB	
Maximum Sample Range	365 m: longitudinal in pulse-echo or 200 m: torsional in pulse-echo	
Maximum Number of Averages	128	
Data Collection	Full Matrix Capture and Broadband	
Focussing Options	C-scan imaging, Time delay focussing	
Display	<ul style="list-style-type: none"> • 26.4cm (10.4in) • Non reflective (AR coating) • Anti-fingerprint (oleophobic coating) • 3mm (1/8in), chemically strengthened glass cover • Optically bonded LCD and touchscreen • Passive backlight enhancement 	
	Software Options	Sonyks GO (Instrument) Sonyks PRO (Optional Laptop Control)
	Laptop Connectivity	Optional connection through Wi-Fi or Gigabit Ethernet
	Storage	200 GB, SSD
	Cooling	Sealed and internal fan
Onboard Pump	60 Psi maximum pressure	
Onboard Collar Pressure Monitoring	Yes	
GPS	Accurate positioning to 2.5m (8.2ft)	
Instrument Transduction Compatibility	Magneto-strictive and Piezo transducer compatibility	
Supported Rings	Sonyks Piezo and Magneto tools, Teletest and other commercial PZT rings	

INSTRUMENT (SUITE)	
Probe Recognition and Setup	Automatic with Sonyks tooling including ring type, size, serial number, pipe and angular orientation
Maximum Sample Range	125 ms
Automated Self-check	Onboard capacitance testing

ENVIRONMENTAL	
IP Rating	Designed for IP65
Operating Temperature	0-40°C (32-104°F)
Operating Humidity	95%, non-condensing
Compliance	ASME, EN 61010-1, CE, WEEE, FCC Part 15B, ICES-003, AS/NZS CISPR 22, RoHS

TOOL AND MODULE TYPES COMPATIBLE	
Piezo Tooling – Transduction Method	Piezo-electric transducers (PZT)
Piezo Tooling – Frequency Range	20-80 kHz broadband collection
Piezo Tooling – Pipe Size Range	6-36in (168.3-914mm) single collar
	26-72in (660-1828mm) dual collar setup
Piezo Tooling – Sensors	Automatic collar recognition, pipe size, orientation and angular position
Piezo Tooling – Max. Surface Temp.	180°C (356°F)
Magneto Tooling – Transduction Method	Segmented Magnetostrictive Sensors (SMS)
Magneto Tooling – Frequency Range	32 kHz – Test range 22-42 kHz
	64 kHz – Test range 54-74 kHz
	128 kHz – Test range 118-138 kHz
Magneto Tooling – Rods Size Range	15.88, 19.05 and 25.4 mm
	(5/8, ¾ and 1 inch)
Magneto Tooling – Pipe Size Range	NPS - 1.5, 2, 2.5, 3, 3.5, 4, 5, 6 and 8 in
	(48.3, 60.3, 73, 88.9, 101.6, 114.3, 141.3, 168.3 and 219.1mm)
	Custom sizes also available.
Magneto Tooling – Maximum Surface Temperature	80°C (176°F) 120°C (248°F) short term
Teletest Tooling – Transduction Method	Piezo-electric transducer (PZT)
Teletest Tooling – Pipe-size	168.3-610 mm (6-24 in) single collar
	660-1321 mm (26-52 in) dual collar setup 1372-1981 mm (54-78 in) treble collar setup
Teletest Tooling – Frequency Range	20-80 kHz depending on spacing and wave mode
Teletest Tooling – Maximum Surface Temperature	High Temperature (HT) 240°C (464°F)
Teletest Module – Wavemode Compatibility	Multimode
	3 ring torsional – 30mm (1.2in)
	3 ring torsional – 45mm (1.8in)

The information contained in this document is accurate as of the date of publication. Eddyfi Technologies reserves the right to modify any product specifications, features, or availability without prior notice. Actual products may vary from those depicted or described herein. All product names, logos, and brands referenced in this document are the property of their respective owners and may be trademarks or registered trademarks of Eddyfi Canada Inc. or its affiliates in Canada, the United States, and/or other countries. For a full list of trademarks, please visit eddyfi.com/en/trademarks. Nothing in this document shall be construed as granting any license or rights under any intellectual property rights of Eddyfi Technologies or any third party. Eddyfi Technologies is a Previa Business Unit.