



Solid State Broadband High Power Amplifier

2126 – BBS2E3KUT

20 – 500 MHz / 1000 Watts

The BBS2E3KUT (SKU 2126) is suitable for multi-octave bandwidth high power CW, modulated, and pulse applications. This amplifier utilizes high power LDMOS devices that provide wide frequency response, high gain, high peak power capability, and low distortions. Exceptional performance, long-term reliability and high efficiency are achieved by employing advanced broadband RF matching networks and combining techniques, EMI/RFI filters, and all qualified components. The amplifier is constructed within one single 5RU drawer including the forced air-cooling. The system comes standard to operate from 180-260VAC single phase or optionally can be ordered with a three phase AC supply.



The amplifier includes a built-in control and monitoring system, with protection functions which preserve high availability. Remote management and diagnostics are via an embedded web server allowing network managed site status and control simply by connecting the unit's Ethernet port to a LAN. Using a web browser and the unit's IP address (IPV4, IPV6) allows ease of access with the benefit of multi-level security. The control system core supports hardware encryption, runs an embedded OS (Linux), has a built-in non-volatile memory for event recording, and factory setup recovery features. The extended memory option allows storage of control parameters and event logs.

Empower RF's ISO9001 Quality Assurance Program assures consistent performance and the highest reliability.

- Solid-state linear design
- Suitable for CW, AM, FM and pulse (Consult factory for other modulation types)
- Compact Modular design
- 50 ohm input/output impedance
- Built in Control, Monitoring and Protection functions
- High reliability and ruggedness
- Optional harmonic and spurious suppression via external switched filter bank (quoted separately)

ELECTRICAL SPECIFICATIONS over temperature conditions (-10 to +50°C)

Parameter	Symbol	Min	Typ	Max	Unit
Operating Frequency	BW	20		500	MHz
Power Output CW ^(Note 1)	P _{SAT}	1000			Watt
Power Output @ 1dB Gain Compression ^(Note 2)	P _{1dB}	500			Watt
Power Gain @ 1dB Gain Compression	G _{1dB}	63			dB
Input Power for Rated P _{SAT}	P _{IN}		0		dBm
Input Power Range	P _{IN}	-3.0		+3.0	dBm
Gain Flatness / Leveled ALC	ΔG			±3.0/±1.0	dB
Gain Adjustment Range	VVA	20			dB
Input Return Loss	S ₁₁			-10	dB
Noise Figure @ maximum gain	NF			15	dB
Third Order Intercept Point 2-Tone @ 54dBm/Tone, 1MHz Spacing	IP3		+64		dBm
Harmonics @ P _{OUT} = 1000W (without Harmonic Suppression Filters)	2 nd 3 rd			-20 -10	dBc
Spurious Signals	Spur			-60	dBc
Operating Voltage – (single Φ)	V _{AC}	180	220	260	Volt
Operating Voltage – (3 Φ)	V _{AC}		208		Volt
Power Consumption @ 1000W CW	P _D			5000	Watt

Notes:
 1. CW measurement performed in MGCC Mode (Manual Gain Control).

2. P1dB measurement performed with CCDF method, IS-95, 1MHz BW.

MECHANICAL SPECIFICATIONS

Parameter	Value	Units
Dimensions W x H x D	17.5 x 8.75 x 22	Inch
Weight (Without Harmonic Suppression Filters)	92	lb.
RF Connectors Input/Output	Input: Type-N, Female Output: Type-7/16-DIN, Female (optional Type-SC, Female)	
RF Sample	Type-SMA, Female	
Blanking Input	Type-BNC, Female	
Cooling	Built in forced-air cooling system	



Solid State Broadband High Power Amplifier

2126 – BBS2E3KUT

20 – 500 MHz / 1000 Watts

ENVIRONMENTAL CHARACTERISTICS (Qualification Data available for review):

Parameter	Symbol	Min	Typ	Max	Unit
Operating Ambient Temperature	T _C	-10		+50	°C
Non-operating Temperature	T _{STG}	-40		+85	°C
Relative Humidity (non-condensing)	RH			95	%
Shock / Vibration - MIL-STD-810F Shock Method 516.5, Vibration Method 514.5	SH / VI				

PROTECTIONS:

Parameter	Specifications	Unit
Input Overdrive	+10 dBm	Max
VSWR Protection	At 3:1 – PA backs-off output power to a safe operating level – no system shutdown, “On Air” time is maximized	-
Thermal – Graceful Degradation	Ambient 50°C	Min
Default Data Recovery	Factory Default Calibration Recovery	

COMMUNICATION INTERFACES:

Function	Utility	Connector
Ethernet	Network management of device / web interface	RJ45
USB	Mass storage / Expansion Bus	USB 1.x/2.0 compatible
RS-232 (default) RS-422 (optional)	Serial management of device / local operator access	D-Sub 9-position Male

SYSTEM I/O CONNECTOR – 14-pin


Pin #	Description	Specifications
1	FWD TP	Forward detected power (analog voltage: 0 – 5 Volt)
2	REV TP	Reverse detected power (analog voltage: 0 – 5 Volt)
3	Summary Fault	Summary Fault: Active TTL Logic Low ($\leq 0.7V$) <i>(Internally Pulled-High)</i>
4	VVA control	Gain control/Monitor: Analog Voltage Range 0-5V Gain Control: 0V= Max. Attenuator, 5V= Min. Attenuator
5	Shutdown	Amplifier Disable: TTL Logic Low ($\leq 0.7V$) = Fault <i>(Internally Pulled-High)</i>
6	Aux P/S TP	$+12.0V_{DC} \pm 2V$ (resettable 0.5amp fuse)
7	Main P/S TP	$+44.0V_{DC} \pm 4.8V$ (resettable 0.5amp fuse)
8	GND	Ground
9	Open drain control	Site management utility (reserved)
10	Open drain control	Site management utility (reserved)
11	Open drain control	Site management utility (reserved)
12	Digital I/O (configurable)	Site management utility (reserved)
13	Digital I/O (configurable)	Site management utility (reserved)
14	GND	Ground

Solid State Broadband High Power Amplifier

2126 – BBS2E3KUT

20 – 500 MHz / 1000 Watts

OUTLINE DRAWING



Note – Outline does not includes optional external filter drawer (Quoted Separately)