

MiniFlex

Ultimate Maneuverability Plumbing Camera



The MiniFlex has been specially developed for inspecting narrow diameter pipes (from 1.25" to 4"). The bullet-shaped camera head and patented Flexi-tube neck make it easy to push the cable through several traps and 90-degree bends. In addition, the system is an entirely portable, all-in-one unit with no stand-alone elements.



Integrated Monitor

- 8" Touchscreen LCD Display
- Image / Video / Audio Recording
- On-screen Text Generator
- Portable Operation up to 7 hours
- On-screen Meter/Footage Counter



Integrated Push Cable and Camera Head

- Wide-angle lens (105° FOV)
- Patented Flexi-tube Neck Capable of P-trap in 1¼" pipe
- Ø 19,5mm (0,75") Detachable Camera Head Working
- Length: 20 - 40 meter (65.6 - 131ft.)
- Built-in 512Hz Sonde
- Waterproof up to 3 bars (100 ft.)



Technical Specifications

Push Cable with Camera Head

Camera head housing	Stainless steel
Diameter	0.76" (19,5 mm)
Viewing angle	105° diagonal
Lens	f=2,1 mm / F10.0
Focus	fixed
Glass	sapphire glass 1 mm
Camera	Color CMOS 400 TV-lines
Sensitivity	1 Lux
Lighting	12 white high power LEDs
512 Hz Sonde	Yes
Water resistance	3 bar
Cable	Combi cable Ø 5,5 mm diameter, 65.6' (20m) and 131' (40m) length (optional 30m length available)
Dimensions	426 mm x 531 mm x 127 mm
Weight (including DVR unit)	9.6 kg

Imaging HUB

Operating on battery	up to 7 hours
Power in	110V AC
Operating temperature	-10 ° C to 45 ° C
Storage temperature	-10 ° C to 60 ° C
Menu languages	Dutch / English / German / French/ Spanish
Display size	8 inch Touchscreen Color
Video out	Yes
Display resolution	1024x768 pixels
Recording resolution	720x576 pixels
Storage	SD card (USB Adapter)
On-screen Text Generator	Yes
On-screen Date and Time Stamp	Yes
Portable Operation	up to 7 hours
On-screen Meter/Footage Counter	Yes

