



## AETECHRON

### CIS-25 Data Sheets

Conducted/Induced Susceptibility  
EMC Testing Kit

#### Kit Includes:

DSR 100-25 Test System

T 1000 Transformer

T 2000 Transformer

T 3700 Transformer

CR 600, Chattering Relay

Two Hours of Expert Consulting

Secure Storage Case

Plus all required cables and connectors



The **CIS-25 Test Kit** combines into a single, complete package the items needed to accurately test to important Aviation standards like DO-160 sections 18 and 19.

Included with the kit are three coupling transformers (T1000, T2000, and T3700), the CR 600 Chattering Relay accessory, and a secure storage cabinet to keep the equipment safe.

The CIS-25 kit also comes with two hours of expert consulting provided by EMC Specialist **Patrick G Andre**, who will answer any questions you might have about set-up or testing.


The DSR 100-25 test system, which is included with the CIS-25 Test Kit, has power in reserve. Each of our DSR Series models provides continuous DC power as rated, and is able to provide 4X rated power for in-rush testing up to 200 ms (such as is required in DO 160 Section 16). Plus, the DSR 100-25 system includes the complete 3110A Standard's Library, so the CIS-25 Test Kit can be used for many other tests.

The equipment is easy to set up and use; all elements in the kit are robust and will provide you with many years of trouble-free service.



## DSR 100-25

### Dropout, Surge, Ripple Simulator and AC/DC Voltage Source



Includes library of 1000+ pre-entered Automotive and Aviation Standards' test routines

Operate as a free-standing system using the included monitor, keyboard and mouse, or control via LAN



Very easy to modify existing tests or build new test sequences

Can function as a controller or node in a larger test system via built-in LAN and GPIO controls

Models from 15A to 200A continuous output current available

#### Key Performance Capabilities:

- 4-Quadrant Can source and sink current
- ±80V DC supply for 12V - 48V systems
- Meets 80V surge requirements
- 300 kHz Sine DC ripple tests for all major standards
- 3µs Rise time exceeds Surge and Drop-out slew rate requirements
- 3mΩ DC source impedance - better than ISO 7637-2 requirements

**AE Techron's DSR 100 Series** systems provide complete, single-box solutions for immunity testing. They include a simple-to-use yet powerful standards waveform generator matched with an industry leading power supply technology and come with an extensive library of tests for many automotive and aviation standards.

All models of the DSR 100 Series are 4-quadrant, allowing them to source and sink current. The DSR Series has power in reserve; each model provides continuous DC power as rated, and is able to provide 4X rated power for in-rush testing up to 200 mS, as is required in DO-160 Section 16.

#### Pre-entered tests for the following Industry standards:

- ANSI ASAE EP455 (Feb03)
- DO 160G (2012-12)
- ISO 7637-2 (2014) (E)
- ISO 7637-2 (2011) (E)
- ISO 16750-2 (2012-11) (E)
- ISO 21780:2020
- JASO D 001-94 (1994-03-31)
- MIL STD 461F (2007-12)
- SAE J1113-2 JUL2004
- SAE J1113-11 JUN2007
- SAE J2139 SEP2005
- SAE J2628 JUL2007

*See page 2 for manufacturer-specific tests.*

## DSR 100 - 25

**Output Current:** 0A to 25A continuous

**Peak Current:** 50A for 200 ms

**Bandwidth (-3dB), Full Signal:** DC to 300 kHz, **Small Signal:** 20Vp-p to 1 MHz

**Supply Voltage:** Single-phase 120V  $\pm$ 10%, 30A, 50/60 Hz; 230V, 15A version available

**Dimensions (DxHxW):** 25 x 9.5 x 20 in. (63.5 x 24.1 x 50.8 cm)

**Weight:** Approximately 76.5 lbs. (35 kg)

## Manufacturer Specific Standards

Audi I EE-32 (2006-06)

BMW GS 95003-2 (2010-01)

BMW GS 95024-2-1 (2010-01)

BMW GS 95024-2-2 (2011-01)

Case New Holland ENS0310 (12-2-2010)

Chrysler CS-11809 (2009-05-29)

Chrysler CS-11979 (2010-04-13)

Claas CN 05 0215 (2004-12)

Cummins 14269 (06201-028)

Cummins 14387 (102020-119)

DAF BSL-003 (1998-12)

DAF BSL-006 (2009-04)

Daimler Chrysler DC-10842 (2003-12)

Daimler Chrysler PF-9326 Change D

Fiat 9-90110 Issue 13 (2007-03)

Ford FMC1278

General Motors GMW3172\_H (July 2010)

Honda 7794Z-SAAA-000 (28.12.2004)

Hyundai ES 39110-00 (2005-08)

Hyundai ES 95400-10 (2007-11-14)

Hyundai ES 96100-02 (2006-11-16)

Mazda MES PW67600 (1995-07)

Mitsubishi ES-X82010 Rev Q (2007-01)

Mitsubishi ES X82115 Rev C (2009-03)

Nissan 28400NDS02 Rev 3 (1999-07)

Nissan 28400NDS03 Rev 3 (2005-08)

Nissan 28401NDS02 Rev 4 (2008-08)

Toyota TSC70212G (2007-06)

Volkswagen VW 80101 (2009-03)

Volkswagen VW 80000 (2009-10)

**Output Range:** -80V to +80V

**Source Impedance:** 3 mV + 2.2  $\mu$ H

**Operation:** 4-quadrant, bi-polar operation

**Output Rise Time:** <3  $\mu$ S

**Remote Control:** GPIO, LAN

**Cooling:** Internal forced-air fans

**Protection:** Over/under voltage, over current, over temperature

**Trigger:** Automatic repeat, manual trigger, external trigger via GPIO or LAN

**Input,**

**Signal In:** BNC connector

**LAN:** Ethernet connector

## Common Data (all models)

**Output,**

**DUT Supply +/-:** High-current connectors

**Signal Output:** BNC connector

**LAN:** Ethernet connector

**Waveforms:** Sine wave sweep, ripple (cranking), DC source, triangle wave, square wave, sawtooth wave

**Control Functions:** Trigger, fixed loop, variable loop, template playback, GPIO output, LAN output

**Operating Environment,**

**Temperature:** 10°C to 50°C (50°F to 122°F), Maximum Output Power de-rated above 30°C (86°F.)

**Humidity:** 70% or less, non-condensing

**Atmospheric Pressure:** 86 kPa (860 mbar) to 106 kPa (1,060 mbar)



230V & 400V versions of this product bear the CE mark



## 3110A Automotive & Aviation Standards Waveform Generator

### Features

- Easiest-to-use LF wave sequence generator
- 1500+ automotive and aviation standard's tests included
- Dramatically reduces test time for repetitive test sequences
- Semi-automatic calibration routine significantly reduces labor-intensive tasks (like CS101)
- Very easy to modify included waveform sequences or create new ones

**AE Techron's 3110A** is a simple-to-use yet powerful standards waveform generator. It has been designed to be used quickly and easily with other AE Techron products to create a wide range of powerful and intelligent EMC test solutions.

The 3110A software is built around the simple concept of a waveform segment. Each waveform segment can have a unique waveform, (sine, square, triangle, and/or DC offset). Frequency, amplitude and DC offset can be clipped, fixed, variable or swept. Segments


The 3110A outputs a standard analog signal that can work with any AE Techron amplifier or other LF amplifiers that you already have. It has a scalable output, so the values entered in the 3110A interface will result in your desired system output. When coupled with the AE Techron model 7234 amplifier, the 3110A can create virtually all waveforms, DC offsets, dropouts and surges needed for EMC tests with rise/ fall times of 1  $\mu$ s or greater and frequencies from DC to 1 MHz.



Microsoft is a trademark of the Microsoft group of companies.

Microsoft  
Partner

Standards Library\AUTOMOTIVE\Ford\FMC1278\CI 230Immunity from Power Cycling, Waveform B (7-1-2015)



Disable Output

Add Wave Add Control

System Status: IDLE

1. DC	x	2. Trigger	x	3. DC	x	4. DC	x	5. DC	x	6. Sine	x	7. DC	x
8. DC	x	9. Trigger	x										

**Wave Properties**

Segment Enabled Calibration

Start Amplitude: 1 Vp Amplitude Sweep: LIN Ripple:

End Amplitude: 1 Vp Clip Amplitude:

Start Frequency: 4 Hz Frequency Sweep: LIN

End Frequency: 4 Hz Phase Angle: 0 deg


Start Offset: 9 Offset Sweep: LIN

End Offset: 9 Duration: 10 Sec

**BUILD A TEST**

Tests are created by combining Wave segments and/or Control segments together. An individual segment within a test, can be as short as 50  $\mu$ s.

Standards Library\AUTOMOTIVE\Toyota\TSC7021G (2007-06)\TSC7021G 5.2 Waveform 14 (+B) IG Operation When Battery Voltage Dropped, 12VDC, (2007-06)



Disable Output

Add Wave Add Control

System Status: IDLE

1. DC	x	2. Trigger	x	3. VL3	x	4. VL1	x	5. DC	x	6. FL2	x	7. DC	x
8. DC	x	9. FL2	x	10. DC	x	11. DC	x	12. DC	x	13. Trigger	x	14. VL1	x
15. VL3	x	16. VL4	x	17. VL5	x	18. DC	x	19. FL6	x	20. DC	x	21. DC	x
22. FL6	x	23. DC	x	24. DC	x	25. DC	x	26. Trigger	x	27. VL5	x	28. VL4	x

**Control Properties**

Type: Linear

All values entered in this Variable Loop must be in the following units:  
 • Amplitude: Vp (Volts Peak)  
 • Frequency: Hz (Hertz)  
 • Offset: VDC (Volts DC)  
 • Duration: ms (Milliseconds)

Variable A: Start: 1 End: -1.001 -By: 0.1 21 Loops

Variable B: Start: 0.5 End: -1.501 -By: 0.1 21 Loops

Variable C: Start: Startin End: Ending By: In/Decr 0 Loops

Variable D: Start: Startin End: Ending By: In/Decr 0 Loops

**WAVE CONTROLS** like Fixed Loop, Variable Loop, and Trigger make the 3110A able to reproduce very complex standards.

The test shown above highlights several key abilities made possible by these wave controls.

A multi-step waveform can start at one level/condition, then be repeated, with up to four variables changing. Single or multi-step

waveforms can be made to repeat (or loop) and these repeating waveforms can be nested within a larger simple or repeating waveform.

At any point during a waveform sequence, the program can be automatically paused (either holding the previous condition or muting) and wait for an external trigger before resuming.

can be calibrated (as required in CS101) and set to continue on to the next segment or to hold for an external trigger. Individual segments can be as short as 50  $\mu$ s.

The power of the system occurs when waveform segments are linked to create test sequences. These test sequences can be of any length and can be run as a single sequence, looped, or looped with multiple variables changing within the test sequence

(as required in multiple Toyota and GM standards). Finally, multiple sequences can be combined to create a single customized extended test.

An extensive library of 1500+ tests for many automotive, aviation and industry Standards makes it possible for the 3110A to save time from day one. And, for customers that require over-testing or testing for products that have no predefined standard, tests from the Standards Library can be easily modified and saved for later use.

## BUILD A SYSTEM

Together, the 3110A and AE Techron amplifiers can be used to create a powerful, modular test system. When used for automotive testing, test system capabilities include 13.5 VDC with a surge potential of up to 100V, or continuous power ratings from 15A to 240A DC. For aviation testing, system capabilities include 14 VDC/28 VDC or 115 VAC/230 VAC with surge voltages up to 360 VAC.



The 3110A delivers extensive capabilities for LF EMC testing with very short training-time requirements. Plus, it makes it easy to automate repetitive and labor-intensive tasks,

making the 3110A a very efficient and cost-effective solution for LF EMC testing.

## Technical Details - Hardware

**Output channels:** 1

**Output Voltage:** 10 Vpk

**Signal Generation:**

**DAC:**

18 bit  
DC – 20 kHz (sine, triangle, sawtooth, and rectangular)  
1  $\mu$ s rise time

**Ripple:**

14 bit  
DC – 1 MHz  
400 Msps  
1% frequency accuracy or better  
1% phase accuracy or better  
1% amplitude accuracy or better

## Control, Status, I/O

**Front Panel:**

**On/Off/Breaker**

**Signal Output:** BNC (analog - 10Vp)

**LED Displays:** Power, System Fault, Signal-In Enabled

**Back Panel:**

**Power Connection:**

120VAC: IEC cable with NEMA 5-15

230VAC: IEC cable with CEE 7/7

**Fuse:** 2A, 250V slow blow (5 mm)

## Physical Characteristics

**Chassis:**

The 3110A is designed for table-top or rack-mounted operation. The chassis is aluminum with a black powder-coat finish. The unit occupies two EIA 19-inch-wide units.

**Weight:** 9.5 lbs (4.31 kg)

**Shipping Weight:** 19.5 lbs (8.85 kg)

**AC Power:**

Single-phase, 120 VAC, 50/60 Hz, 2A service;

230 VAC, 50/60 Hz, 2A model available

**Dimensions:**

19 in. x 11.75 in. x 3.5 in.  
(48.3 cm x 29.8 cm x 8.9 cm)

## Technical Highlights – Software

**Waveforms Supported:**

Sine, Ripple, DC, Triangle, Square, Rectangular, Sawtooth

**Waveform Modifiers:**

Amplitude, frequency and DC offset (fixed or linear, logarithmic\* or exponential sweep); phase angle; duration; clipped amplitude; and ripple on AC

**Waveform Controls:**

Trigger (user, GPIO, LAN), Fixed Loop, Variable Loop, Scripted Variable Loop, Template Playback, GPIO Output, LAN Output

**Minimum Step Size (isolated):**

25  $\mu$ s  $\pm$ 3  $\mu$ s

**DC Quiescent Noise:**

5 mV<sub>p-p</sub>

**Test Capabilities,**

**Minimum Waveform Duration:** 50  $\mu$ s


**Maximum Number of Loop Repeats:** >1 million

**Storage Capabilities, Number of Tests:**

300,000 (expandable to 1 million)

See Capabilities sheet for loop characteristics

\*Logarithmic sweep available for sine, ripple and DC offset waveforms only.





## T1000 Transformer for Magnetic-Field Susceptibility Testing

### For testing to these Specifications:

- DO 160 Section 19
- Boeing D6-16050-5 Section 7.2

### Features

- Up to 100 A<sub>RMS</sub> secondary current
- Exceeds AF Magnetic Field test requirements of DO 160 Section 19 and Boeing D6-16050-5 Section 7.2
- Circuit breaker protected from over-current
- Durable steel and high-density polyethylene case for impact resistance

The AE Techron **T1000 Magnetic-Field Susceptibility Transformer** was designed to exceed the AF Magnetic Field susceptibility test requirements of DO 160 Section 19 and Boeing D6-16050-5 Section 7.2.

It may also be used as 10-to-1 step-down transformer for output currents of up to 100 A<sub>RMS</sub>.

The T1000 transformer provides up to 300 A-m and is able to generate up to 100A. The turns ratio provides a ten-to-one step down to the secondary winding.

The T1000 provides convenient input connectors via binding posts. Standard 0.75-inch spacing of binding posts allows use of standard plugs. Output is via Multi Contact 125A plugs.

A 12-amp circuit breaker protects the unit against over-current conditions. A rugged, impact-resistant case and robust design protects the transformer from accidental damage.

The T1000 transformer is for use by experienced staff.




Figure 1 – T1000 Maximum SOA (safe operating area)




Figure 2 – Sample Application: DO 160 Section 19 Test Load Wiring

## Specifications

### Performance Specifications

**Primary:**

200 V<sub>p</sub> maximum

**Secondary:**

20.0 V<sub>p</sub> maximum output

**Dielectric Test:**

1200 VDC

**Turns Ratio::**

Ten-to-one step down

**Protection:**

Input power-protected via circuit breaker

### Controls and Connectors

(see Figure 3)

**Input Terminals:**

4-way binding posts

**Output Terminals:**

Multi Contact 125A plugs

**Circuit Breaker:**

Primary input limited to 12A; push to reset

### Physical Characteristics

**Case:**

Steel interior shell with a durable external shell made from high-density polyethylene for impact resistance.




Figure 3 – T1000 Controls and Connectors

### Operating Conditions,

**Temperature:** 10°C to 40°C (50°F to 104°F)

**Humidity:** 70% or less, non-condensing

### Recommended Ambient Temperature:

25°C (77°F)

### Cooling:

Natural air convection

### Weight:

15 lbs. (6.8 kg)

### Dimensions (WxDxH):

5.25 in. x 10.375 in. x 9.75 in. (13.3 cm x 26.4 cm x 24.8 cm)

*AE Techron Sales Representative*



## T2000 Transformer for LF Conducted Susceptibility Testing

### Features

- Frequency response – 10 Hz to 250 kHz
- Turns ratio – 2:1 step down
- Audio power – 200W MAX
- Meets the LF Conducted Susceptibility test requirements of DO 160 Section 18
- Circuit breaker protected from over-current on secondary
- Durable steel and high-density polyethylene case for impact resistance

### For testing to these Specifications:

- Chrysler CS-11809 (2009)
- DaimlerChrysler DC-10615
- DO 160 Section 16
- DO 160 Section 18
- Ford FMC 1278
- GLloyd VI-7-2
- ISO 11452-10
- EMC-CS-2010JLR V1.1 (2011-01)
- MIL STD 461 D CS 101
- MIL STD 461 D CS 109
- MIL STD 461 E CS 101
- MIL STD 461 E CS 109
- MIL STD 461 F CS 101
- MIL STD 461 F CS 109
- MIL-STD-704
- Mitsubishi ES-X82115
- SAE J1113-2
- Tata TST/TS/WI/257

The AE Techron **T2000 Audio-Bandwidth Transformer** was designed to meet or exceed the LF conducted susceptibility test requirements of DO 160 Section 18. The T2000 is used to apply the required test signals to the lines under test for ripple voltage tests and continuous or transient conducted immunity tests.

It may also be used as 2-to-1 step-down transformer. The secondary can support up to 40 A<sub>P</sub>.

The T2000 transformer supports up to 200W and is able to pass up to 40 A<sub>P</sub> on the secondary. The turns ratio provides a two-to-one step down.

The T2000 provides convenient input connectors via binding posts. Standard 0.75-inch spacing of binding posts allows use of standard plugs. Output is via Multi Contact 125A plugs.

A thermal breaker protects the unit against over-current conditions on the primary. A 35A<sub>RMS</sub> breaker protects the unit against over-current conditions on the secondary. A rugged, impact-resistant case and robust design protects the transformer from accidental damage.

The T2000 transformer is for use by experienced staff.




Figure 1 – Sample Application: DO 160 Section 18 Test Setup (for AC and DC power lines, differential mode)

## Specifications

### Performance Specifications

#### Transformer DC Resistance,

##### Primary:

0.076 ohms

##### Secondary:

0.021 ohms

#### Frequency Response:

10 Hz to 250 kHz

#### Audio Power:

200W

#### Dielectric Test:

1500 VDC primary to secondary

#### Secondary Saturation:

40A<sub>P</sub> AC or DC maximum

#### Turns Ratio::

Two-to-one step down

#### Secondary Inductance:

Approximately 0.6 mH (unloaded)




Figure 2 – T2000 Controls and Connectors

#### Protection:

Input power-protected via thermal breaker; secondary winding protected via 35A<sub>RMS</sub> breaker

---

## Controls and Connectors

(see **Figure 2**)

### Input Terminals:

4-way binding posts

### Output Terminals:

Multi Contact 125A plugs

### Circuit Breaker:

Secondary winding limited to 35A<sub>RMS</sub> via circuit breaker; push to reset.

## Physical Characteristics

### Case:

Steel interior shell with a durable external shell made from high-density polyethylene for impact resistance.

## Operating Conditions,

**Temperature:** 10°C to 40°C (50°F to 104°F)

**Humidity:** 70% or less, non-condensing

### Recommended Ambient Temperature:

25°C (77°F)

### Cooling:

Natural air convection

### Weight:

17 lbs. (7.7 kg)

### Dimensions (WxDxH):

5.25 in. x 10.375 in. x 9.75 in. (13.3 cm x 26.4 cm x 24.8 cm)

*AE Techron Sales Representative*



## T3700 Transformer for Electric-Field Susceptibility Testing

### For testing to these Specifications:

- DO 160 Section 19
- Boeing D6-16050-5 Section 7.2

### Features

- Up to 3,700  $V_{RMS}$
- Meets or exceeds voltage requirements of DO 160 Section 19 and Boeing D6-16050-5 Section 7.2
- Robust design, withstand tested to 5,000 VDC
- Durable steel and high-density polyethylene case for impact resistance

The AE Techron **T3700 Electric-Field Susceptibility Transformer** was designed to meet or exceed the voltage requirements of DO 160 Section 19 and Boeing D6-16050-5 Section 7.2 testing.

It may also be used as a 1-to-37 step-up transformer for voltages up to 3700  $V_{RMS}$ .

The T3700 transformer is able to generate up to a 3700  $V_{RMS}$  potential. It is withstand tested to 135% of rated output to ensure a long, trouble-free life. The turns ratio provides a 1-to-37 step up to the secondary winding.

The T3700 provides convenient input connectors via touch-proof, four-way binding posts. Standard 0.75-inch spacing of binding posts allows use of standard plugs.

A 1-amp fuse protects the unit against over-current conditions. A rugged, impact-resistant case and robust design protects the transformer from accidental damage.

The T3700's voltage output meets or exceeds the requirements of DO 160 Section 19 and Boeing D6-16050-5 Section 7.2. It is safe for use by experienced staff.




Figure 1 – T3700 Maximum SOA (safe operating area)




Figure 2 – DO 160 Section 19 Test Load Wiring




Figure 3 – Physical and Apparent Turns Ratios vs. Frequency




Figure 4 – T3700 Controls and Connectors

## Specifications

### Performance Specifications

#### Primary:

100  $V_{RMS}$  maximum or 1  $A_{RMS}$ , maximum

#### Secondary:

3700  $V_{RMS}$  maximum output

#### Physical Turns Ratio:

1-to-37 step up

#### Dielectric Test:

5 kVDC primary to case

5 kVDC secondary to case

#### Frequency Range:

250 Hz to 35 kHz

#### Protection:

Current-protected input

### Controls and Connectors

(see Figure 4)

#### Input Terminals:

4-way binding posts

#### Output Terminals:

LGH high-voltage connector (+)

Banana jack (-)

#### Over-Current Protection:

Primary input limited via fuse to 1A (T1A H 250V)

#### Grounding Lug:

Screw terminal grounding connector. Connect to earth ground using appropriate wire and connector.

---

## Physical Characteristics

**Case:**

Steel interior shell with a durable external shell made from high-density polyethylene for impact resistance.

**Operating Conditions,**

**Temperature:** 10°C to 40°C (50°F to 104°F)

**Humidity:** 70% or less, non-condensing

**Recommended Ambient Temperature:**

25°C (77°F)

**Cooling:**

Natural air convection

**Weight:**

16 lbs. (7.3 kg)

**Dimensions (WxDxH):**

5.25 in. x 10.375 in. x 9.75 in. (13.3 cm x 26.4 cm x 24.8 cm)

*AE Techron Sales Representative*



# CR 600 Chattering Relay

for DO-160 Section 19.3.5 Testing

## Features

- Coil Voltage: 24 VDC
- Coil Current: 84 mA
- Contact Rating: 30A
- Typical Pulse Voltage: >700 Vpp
- Includes oscilloscope connection points for voltage monitoring




Figure 1 – Example of output from the CR 600 when adjusted to yield a pulse repetition rate of eight to ten pulses per second




Figure 2 – Example of output from the CR 600 when adjusted for a pulse sequence with an amplitude greater than or equal to 600 Vpp, and a total duration of 50 to 1000 microseconds




Figure 3 – Example of output from the CR 600 when adjusted for a repetition period of 0.2 to 10 microseconds

The AE Techron **CR 600 Chattering Relay** is a cost-effective, rugged yet elegant solution to the DO 160 Section 19.3.5 “Spikes Induced into Interconnecting Cables” test requirement.

Internally built around a 50A high-current relay with two independent sets of contacts, the CR 600 was engineered for double the life before refurbishment.

The CR 600 uses quick-connect, touch-proof connectors to ensure efficient setup and a safe test environment. It also includes quick-clip test points for oscilloscope monitoring of tests in progress.

When driven from an intermittent voltage source like the AE Techron DSR 100-25 and utilizing test waveform, “Section 19.3.5 CR 600”, the CR 600 output meets the voltage (600V), duration (50 – 1000 μs) and repetition-period (0.2 to 10 μs) requirements specified by the DO-160 standard.

### For testing to these Specifications:

- DO 160 Section 19.3.5

## Product Specifications

### Performance

**Coil Voltage:** 24 VDC

**Coil Current:** 84 mA

**Contact Rating:** 30A




Figure 2 – Sample Application: Test Setup for RTCA DO160 Section 19.3.5 using the CR 600

**Typical Pulse Voltage:** >700 Vpp

### Controls and Connectors

**Amplifier Connections:**

Dual binding posts

**Radiating Loop:**

Dual binding posts

**Oscilloscope:**

Dual turret connectors

### Physical Characteristics

**Case:**

Injection-molded plastic

**Operating Conditions,**

**Temperature:** 10°C to 40°C (50°F to 104°F)

**Humidity:** 70% or less, non-condensing

**Recommended Ambient Temperature:**

25°C (77°F)

**Cooling:**

Natural air convection




Figure 3 – CR 600 Connectors

**Weight:**

1.5 lbs. (0.68 kg)

**Dimensions (HxWxD):**

3.25 in. x 6.25 in. x 7.25 in. (8.3 cm x 15.9 cm x 18.4 cm)

*AE Techron Sales Representative*