

Advanced Test Equipment Corp.

Rentals • Sales • Calibration • Service





PRODUCT DATA SHEET

C3908

4-Port Dual Directional Coupler employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

Electrical Specifications:

Mechanical Specifications:

Type: Connectorized Material: Aluminum 6061-T6

Surface Finish: Chem. Film Per MIL-DTL-5541F

Type I Class 3 (Yellow Iridite) RoHS Compliant Available

Operating Temperature: -55°C to $+75^{\circ}\text{C}$ Storage Temperature: -60°C to $+85^{\circ}\text{C}$ Humidity: 95% Non-Condensing Size: $3.0 \times 3.0 \times 1.09$ "

Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C3908-10	N Female	N Female	N Female	N Female
C3908-12	N Female	N Female	SMA	SMA
C3908-13	N Female	N Female	BNC	BNC
C3908-20	7/16 Female	7/16 Female	N Female	N Female
C3908-22	7/16 Female	7/16 Female	SMA	SMA
C3908-23	7/16 Female	7/16 Female	BNC	BNC
C3908-610	N Female	N Male	N Female	N Female
C3908-627	7/16 Female	7/16 Male	N Female	N Female
C3908-712	N Male	N Female	SMA	SMA
C3908-714	N Male	N Female	N Female	N Female
C3908-727	7/16 Male	7/16 Female	N Female	N Female
C3908-728	7/16 Male	7/16 Female	SMA	SMA


(7/16-F Main Line connector option increases size to 3.0 x 3.0 x 1.59")






PRODUCT DATA SHEET C3908


Performance Data (Specifications subject to change without notice):








Directivity:



Frequency (MHz)



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com