



Advanced Test Equipment Corp.

www.atecorp.com 800-404-ATEC (2832)



A.H. Systems, Inc.

9710 Cozycroft Ave.
Chatsworth, CA 91311



Tel: (818) 998-0223

Fax: (818) 998-6892

◆ sales@AHSystems.com

◆ www.AHSystems.com

SAC-26G

**Low-Loss, High-Frequency RF
cable for high frequency testing**
up to 26.5 GHz

Our Low-Loss High-Frequency flexible cables are the preferred choice over standard cable types. With improved power handling, low VSWR, and high frequency capabilities, the Low-Loss cables can be made to your specified length and delivered in two days.



Frequency Range: DC – 26.5 GHz

Impedance: 50 ohm

Capacitance: 25.0 pF/ft

Velocity: 80-83%

RF leakage: >95dB to 18 GHz

Typical VSWR: 1.5:1 up to 26 GHz

Max Power @ 1 GHz: 720 watts

Max Power @ 10 GHz: 220 watts

Standard connectors: SMA, male

Standard Cable Length: 3 Meters (custom lengths made upon request)

Physical Dimensions

Cable size (O.D.): 0.195in. (4.95mm)

Weight: 4.4 lbs./100 ft (2.0 Kg / 30m)

Minimum bend radius: 1.0 in. (25mm)

Temp Range -55° to +200° C

Features

- 26 GHz frequency
- Individually Calibrated
- Low Attenuation, Low VSWR
- Customize length cables made to your specifications

AH Systems assembles high performance microwave cable that utilizes only the very best materials. With plenty of raw stock on hand, we can create a custom length high precision cable assembly within a few days. The outer jacket is a tough, high temperature thermoplastic that can withstand temperatures from -55° to +200° Celsius. All this adds up to a very superior microwave cable product that can meet the most demanding requirements. This product line has three different sizes of cable designed to operate from DC up to 18, 26 or 40 GHz. Please call us and discuss your needs with one of our design engineers.



A.H. Systems, Inc.

9710 Cozycroft Ave.
Chatsworth, CA 91311



Tel: (818) 998-0223
Fax: (818) 998-6892

◆ sales@AHSystems.com
◆ www.AHSystems.com

3 Meter Low Loss Cable
Attenuation Model: SAC-26G-3

