



Features / Benefits

- Refrigerant R410A
- High-efficiency shell and tube evaporators
- Three phase
- Scroll compressors
- Free-cooling version available



Product Specifications

CAPACITIES		0062	0076	0092	0117	0141	0178
Cooling Capacity	ton	6.2	7.6	9.2	11.7	14.1	17.8
Capacity based on 45°F water outlet temp.; 10°F delta t @ 95° ambient temperature							
BTU/hr		74,552	90,707	110,890	140,638	167,777	214,057
Reservoir Capacity	gal	32	58	58	58	58	92
Compressors/Circuits/Fans		1/1/1	1/1/2	1/1/2	1/1/2	1/1/2	2/1/3

DIMENSIONS		0062	0076	0092	0117	0141	0178
Length	in	56	74	74	74	74	97
Width	in	30	31	31	31	31	36
Height	in	63	65	65	65	65	78
Weight (Dry)	lbs	727	970	975	1,014	1,135	1,587

ELECTRICAL		0062	0076	0092	0117	0141	0178
Volts		460	460	460	460	460	460
Phase		3	3	3	3	3	3
Hertz		60	60	60	60	60	60
FLA		20.2	25.0	26.9	31.8	38.2	46.3

MISC SPECS		0062	0076	0092	0117	0141	0178
Refrigerant		R410A	R410A	R410A	R410A	R410A	R410A
Head Pressure	psi	60	70	70	70	70	70
Flow, Nominal	gpm	16	20	25	30	35	45
Fluid Connections	MPT	1-1/2"	1-1/2"	1-1/2"	1-1/2"	1-1/2"	2"



Features / Benefits

- Refrigerant R410A
- High-efficiency shell and tube evaporators
- Three phase
- Scroll compressors
- Free-cooling version available



Product Specifications

CAPACITIES		0201	0229	0282	0353	0395	0450
Cooling Capacity	ton	20.1	22.9	28.2	35.3	39.5	45
Capacity based on 45°F water outlet temp.; 10°F delta t @ 95° ambient temperature							
BTU/hr		240,955	275,155	338,397	424,050	474,037	540,173
Reservoir Capacity	gal	92	92	92	132	132	132
Compressors/Circuits/Fans		2/1/3	2/1/3	2/1/3	2/2/2	2/2/2	2/2/2

DIMENSIONS		0201	0229	0282	0353	0395	0450
Length	in	97	97	97	137	137	137
Width	in	36	36	36	48	48	48
Height	in	78	78	78	78	78	78
Weight (Dry)	lbs	1,653	1,653	1,725	2,050	2,175	2,300

ELECTRICAL		0201	0229	0282	0353	0395	0450
Volts		460	460	460	460	460	460
Phase		3	3	3	3	3	3
Hertz		60	60	60	60	60	60
FLA		51.6	61.1	79.4	93.2	101.5	147.0

MISC SPECS		0201	0229	0282	0353	0395	0450
Refrigerant		R410A	R410A	R410A	R410A	R410A	R410A
Head Pressure	psi	65	65	65	65	65	65
Flow, Nominal	gpm	55	60	72	96	108	123
Fluid Connections	MPT	2"	2"	2"	2-1/2"	2-1/2"	2-1/2"